

Hale Trailer Brake & Wheel

A000090-A000091



EAST GENESIS UNLOADER TRAILER



OPEN TOP CLOSED TOP

BODY: "GENESIS"		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAXLE-2 FIXED-1 LIFT
LENGTH (FEET)	50	TYPE	SPLIT VAN DOORS	TYPE	ALUM SUB FRAME (11)
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.100	REAR AXLE SETTING	54"
FRONT	0.150	S / S HINGE ON	SPLIT DOOR 4-3-4	5TH WHEEL HT	49"
MIDDLE	0.150	GATESEAL	N/A	PIN SETTING	36" W/ 3/8" PLATE
REAR	0.150	GATE LADDER	N/A	SUSPENSION	AAT30K/E1-2 L LIFT-E3
POLISHED SIDES	NONE	TARP HOOKS	NONE	SPRINGS	AIR(16)(17)(18)(19)(20)
ROOF	NONE	WINDERS	N/A	AXLES	TP
ROOF MAT'L	NONE	GATE GUIDE	N/A	BRAKES	16-1/2" x 7"
BULKHEAD	3/16" (1)(6)(7)(8)(9)	GATE CONTROL	DBL LOCK RODS	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO (14)	ABS	2S / 1M
TARP	NONE		MIDDLE-SPRING STYLE	HUBS	10 S STEEL / CAST
CATWALK	YES- INTERMEDIATE		REAR-TUBE STYLE		PIL- EAST ELITE
B.H. LADDER	COMMERCIAL-D/S	COMPACTOR:		WHEELS	8.25 X 24.5 6 STEEL/
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		6 CLEAN BUFF (21)
FLOOR MAKE	KEITH - 3.5" DRIVES	CENTER LATCH		TIRES	11R 24.5 GRABBER OA
FLOOR MAT'L	#2299 - 1/2" IMPACT	PIN DIA.			H 16 PLY GENER.(22)
WEARPADS	CWS (15)	HYDRAULICS:		DOLLIES	2 SPEED JOST A451
TAPE COLOR	NONE	HOSES	TWO-4000 PSI	LOCATION	D/S CRANK (23)
LIGHT PANEL	LED IN BODY (12)	LENGTH	108"	BUMPER	EAST UNDERRIDE
MARKER LIGHTS	LED (13)	FITTINGS	WINGNUT	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	HP	1" MALE	PUSH BLOCKS	YES
MUDFLAPS	YES	LP	1" FEMALE	PAINT	BLACK
HOSE HANGER	YES	HOSE LOCATION	P/S-REF PIC BELOW		
TIRE CARRIER	YES-P/S	AIR & ELECTRICAL	CENTER (2)(3)(5)		

REMARKS:

1. FOUR CAST STEPS INSIDE OF BULKHEAD OPPOSITE OUTSIDE LADDER ON D/S. HIGHEST STEP TO BE 24" DOWN FROM TOP OF THE BULKHEAD.
2. RIGHT WEIGH OIL FILLED GAUGE (LBS.) MOUNTED ON NOSE TOWARDS D/S- REFERENCE PIC BELOW.
3. FILTERED GLADHANDS
5. ADD AUXILIARY ISO 7 WAY PLUG LABELED '7 WAY ISO'.
6. MANDOOR IN CENTER OF BULKHEAD.
7. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL
8. KEITH ALUMINUM SUBFRAME. STAINLESS STEEL HYDRAULIC TUBING. WITH DRIVE UNIT BRACES.
9. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
10. FLOOR OPENING MOVED FORWARD FOR TRIDEM, MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES, NOTE AXLE SPACING AND SETTINGS.
11. EXTEND SUBFRAME AS NEEDED TO ACCOMMODATE AXLE SPACING AND HAVE ALL AXLES MISS DRIVE UNIT.
12. LIGHT PANEL IN BODY AND TO HAVE LED BACK UP LIGHTS OOOX ooo XOOO
13. LED - 5 PR 30385Y/R MARKER LIGHTS BOTTOM AND TOP W/ PROTECTORS.
14. REAR CROSSPIPE WILL BE IN STANDARD PLACEMENT.
15. NYLON T BLOCKS
16. AAT30K FOR AXLES #1 & #2 AND AAL30K LIFT AXLE AS AXLE #3 (REAR AXLE) - ALL AXLES TO EQUALIZE.
17. REAR LIFTING AXLE TO HAVE BRAKE RELEASE VALVE - REAR AXLE ACTUATED WITH FRAME SWITCH + ELEC CC (WIRED THROUGH AUX. PLUG)
18. ALL CONTROLS TO BE IN WEATHER TIGHT POLYCARBONATE BOX (AMP 1086LF) AHEAD OF AXLE #1 AND WIRED FOR CC THROUGH AUX PLUG-REF.69464.
19. GALVANIZED SUSPENSION HANGERS.
20. NO CROSSOVER KIT FOR SUSPENSION.
21. WHEEL GUARD INSULATORS.
22. TIREMAXX PRO ON ALL AXLES.
23. C/L OF LANDING GEAR TO BE 34' FROM REAR EDGE OF FLOOR (2' REARWARD OF STD POSITION DUE TO TIPPER PLATFORM REQUEST)
24. KEITH 2299 FLOOR TO HAVE STEEL INSERTS BOTH ENDS OF SLAT INSTALLED BY KEITH
25. 24" X 24" X 48" SMOOTH DOUBLE DOOR TOOLBOX AERO WEATHER EXTREME 3/16" WITH CAMLOCKS ON D/S
26. KEITH SPLASH GUARD BEARINGS FULL LENGTH.

OVERALL HEIGHT (FT) **31.25** **EMPTY WEIGHT (#)** **20,945** **CUBIC YARDS** **130**
 (EMPTY WEIGHT VARIANCE +/- 3%)



DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.