


Hale Trailer Brake & Wheel A000530-A000532


XL Blademate

XL SPECIALIZED TRAILERS



MODEL OVERALL LENGTH OVERALL WIDTH CAPACITY

XL 90 BM 53' 102" 85,000 LB CLOSED DISTRIBUTED



GOOSENECK

LENGTH 9' KINGPIN SETTING 19" SWING CLEARANCE 77" **5TH WHEEL HEIGHT** 49" 2 SPEED LANDING GEAR - HANDLE ON CURBSIDE LANDING GEAR FENDERS BOLT ON ALUMINUM FRONT FENDERS D-RINGS (2) D-RINGS ON FRONT (2) D-RINGS PER SIDE - 4 TOTAL (4) D-RINGS ON REAR OF GOOSENECK PLATFORM 48" LOADING PLATFORM ON FRONT DECK HEIGHT 57" DECK HEIGHT ON PLATFORM

MAIN DECK

LENGTH

BUMPER

D-RINGS

PLAT FORM

MAIN FRAME

OPENS TO 184' 2" WITH PULLOUT BUMPER LOADED DECK HEIGHT 51" 18" STEEL PLATFORM AT REAR W/ 4 D-RINGS TELESCOPING MAIN FRAME (4 TOTAL SECTIONS) FLAG HOLDERS (3) PAIR OF FLAG HOLDERS 20' PULLOUT BUMPER WITH STOPS ON 24" CENTERS - NON LOAD BEARING BUMPER (1) PAIR IN TAIL CHANNEL

REAR DECK

AXLES	(3) 25,000 NOMINAL, 80" TRACKING
SUSPENSION	HEND-TURNER / 25,000 AIR
AXLE SPACING	71"
ABS	2S1M SPRING BRAKES ON 1 AXLES
TIRES	245 / 70R / 17.5
WHEELS	6.75 X 17.5 / STEEL DISC WHEELS
BRAKES	12 1/4" X 7 1/2"
DRUMS	HUB PILOT/OUTBOARD DRUMS
ELECTRICAL	12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT PACKAGE
MUD FLAPS	MINIMIZER WHEEL COVER OVER EACH AXLE WITH MUDFLAP

PAINT

BLACK, RED, CAT YELLOW, XL WHITE OR CUSTOM

ADDITIONAL

LIQUID FILLED AIR GAUGE 13 HP HYDRAULIC POWER UNIT LODAR REMOTE FOR STEERING 4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT PSI TIRE INFLATION SYSTEM RAISE & LOWER VALVE

48" ROLLING BUNK, 55" HEIGHT, OVER REAR MOST BEAM ONLY

BASE WEIGHT 32,300 LB

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.