

## Hale Trailer Brake & Wheel A001197-A001198



Item (	Qty	Description
ART-60-40		40' 12"x4" Main Frame Serial 4"x4"x1/4" Stabilizer Frame w/ 4"x4"x1/4" Angle Wrap 3/8" Top Frame Wrap, 3/4" Bottom Frame Wrap 12"x4" Truss Frame Mounted Beneath Main Frame (2) 8" Dia Telescopic Lift Cylinders (2) 7" Dia. Double Acting Reeve Cylinders Manual External Valve w. Pressure Gauge All Hydraulic Lines-IC Fittings and Nylon Covering 50,000 lbs. Hutch H-900 Single Point Suspension (2) 25,000 lbs. Meritor Axles,
	1 1 1 1	16"x7" Auto Slack Brakes ABS 2S1M  (2) Fixed Stops at Front of Trailer  3 1/2" Rollers Welded to Outside of Frame  (4) Nylon Tie Down Straps- Customer Specification  Truckle L.E.D DOT Approved Lighting and Harnesses  New 10- Hole Uni-mount Hubs, Drums, & Steel Rims w. 11R22.5 Tires (8)  FM No. 223 ICC bumper- Air Actuated  L.E.D Frame-Up Alarm- Strobe  Cleaned, Primed, Painted- Industrial Enamel: Black  Roll Rite Hydraulic Taping System with an ACE Telescoping Tower  Removable Stops Complete Assembly  Tool Box- 18"x18"x24"- Steel (Black)  Automatic Tire Inflatation System  L.E.D. Work Lights (2) Mounted- Side tarp Arm Mounts