



Hale Trailer Brake & Wheel

001223-001224

25ART			
25 Ton Tridem Air Tilt/Air Ramp			
Tags			
		Base Weight:	12,300
TRAILER			
	Overall Length	37 ft. 6 in.	
	Overall Width	102 in.	
	Weight lbs +/- 2%	12675, including options	
	A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam	
	Hitch	3 in. pintle eye, adjustable 5 position 17 in. to 28 in.	
DECK			
	Deck Length	24 ft.	
	Loaded Deck Height	34 in.	
	Main Frame	Hi-Tensile Wide Flange 14 in. @ 22	
	Cross Members	Hi-Tensile 6 in. Channel @ 8.2	
	Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside	
	Air Tilt Deck	2 Air Bags	
	Floor	1 3/8 in. x 7 in. Keruing Shiplapped	
	Landing Gear	Dual 2 Speed	
SUSPENSION/AXLES			
	Axles	25,000 lbs Capacity 77.5 in. Track 3/4 in. wall ,1 Lift Axle with Control Box	
	Spread	49 in.	
	Suspension	Hutch 9700 spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge and dump valve)	
	Brakes	Quick Change 12 1/4 in. x 7 in.	
	Brake Chamber	#3030, All Axles	
	Air Brake System	2S/1M	
	Bearings	Oil Bath	
	Slack Adjusters	Automatic	
	Hubs & Drums	8 Stud Unimount C / W Cast Drums	
	Tires	235/75R17.5	
	Wheels	6.75 x 17.5 Steel Disc - Painted White	
BEAVERTAIL			
	Length	6 ft. @ 6 degree slope, Planked in	
RAMPS			
	Length	38 in. x 76 in. Air Operated Planked	
GENERAL SPECIFICATIONS			
	Electrical System	Modular, Vapor Proof GROTE Ultra Blue	
	Lights	LED CMVSS 108 / FMVSS 108	
	Front Connector	SAE J560 7 Pin	
	Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked	
	Color	Black	
	Mudflaps	1 set of BWS at rear	
	Toolbox	Full A Frame mounted with solid bottom and cover	
	Load Securement	8 pair of D-rings: location is 7 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard	
	Fenders	3/16 in. deck plate	

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.