



Hale Trailer Brake & Wheel 001463-001464

20ANR

20 Ton Tandem Air Tilt/No Ramp

Tags

TRAILER

 Overall Length
 33 ft. 7 in.

 Overall Width
 102 in.

 Weight lbs +/- 2%
 9918

A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam

Hitch 3 in. pintle eye, adjustable 5 position 17 in. to 28 in.

DECK

Deck Length 20 ft. Loaded Deck Height 34 in.

Main Frame Hi-Tensile Wide Flange 14 in. @ 22

Cross Members Hi-Tensile 6 in. Channel @ 8.2

Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside

Air Tilt Deck 2 Air Bags

Floor 1 3/8 in. x 7 in. Keruing Shiplapped

Landing Gear Dual 2 Speed

Rear Wedge Style bumper with air assisted tilt deck for ground loading

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall

Spread 49 in.

SuspensionHutch 9700 spring rideBrakesQuick Change 12 1/4 in. x 7 in.

Brake Chamber #3030, All Axles

Air Brake System 2S/1M

Bearings Oil Bath

Slack Adjusters Automatic

Hubs & Drums8 Stud Unimount C / W Cast DrumsTiresTire Upgrade to 235/75R17.5

Wheels 6.75 x 17.5 Steel Disc - Painted White

BEAVERTAIL

Length 6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue

Lights LED CMVSS 108 / FMVSS 108

Front Connector SAE J560 7 Pin

Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked

Color Black

Mudflaps 1 set of BWS at rear

Toolbox Full A Frame mounted with solid bottom and cover

Load Securement5 pair of D-ringsFenders3/16 in. deck plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment