



# Hale Trailer Brake & Wheel

001508-001510



## 20NTT

### 20 Ton Tandem Non Tilt

#### Tags

#### TRAILER

Overall Length	*NPO*: 34 ft 8 in.
Overall Width	102 in.
Weight lbs +/- 2%	8205
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch	3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

#### DECK

Deck Length	21 ft.
Loaded Deck Height	34 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 22
Cross Members	Hi-Tensile 5 in. Channel @ 6.7
Side Rail	Hi-Tensile 7 in. Channel @ 9.8 open on inside
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	Dual 2 Speed

#### SUSPENSION/AXLES

Axles	25,000 lbs Capacity 77.5 in. Track 3/4 in. wall
Spread	49 in.
Suspension	Hutch 9700 spring ride
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	215/75R17.5
Wheels	6.75 x 17.5 Steel Disc - Painted White

#### BEAVERTAIL

Length	*NPO*: 6 ft. Beavertail, planked
--------	----------------------------------

#### RAMPS

Length	*NPO*: 20 in. x 60 in. Spring assist with 3rd spring, wood filled with grab handles
--------	---

#### GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Lights	LED CMVSS 108 / FMVSS 108
Front Connector	SAE J560 7 Pin
Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color	Black
Load Securement	4 pair of D-rings
Toolbox	Standard Mesh with no cover
Fenders	3/16 in. deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.