

Hale Trailer Brake & Wheel A001882-A001885



REGION DOMESTIC

LOAD PROFILE 72K
VESSEL THICKNESS 0.165 5454-H32 ALUMINUM

CUBIC FT CAPACITY 1000
COMMODITY CEMENT
TRAILER OPERATION TYPE PNEUMATIC

TRAILER OPERATION TYPE PNEUMATIC
FOOD GRADE NONE
VESSEL FINISH MILLED

LENGTH 42 FT. / 12.80 M.

WIDTH 102

OPERATING TEMPERATURE 185 F / 85 C

OPERATING PRESSURE 14.7 PSI / 101.35 KPA
COMPARTMENT OPTIONS SINGLE COMPARTMENT
LOWER HOPPER CONES WELD-ON 45 DEG (STANDARD)

MANLID QUANTITY

MANLID LOCATION LAYOUT CENTER ONLY

FIRST MANLID TYPE BETTS MODEL 8555, 20 IN. MANWAY

SECOND MANLID TYPE NONE

AERATION

AERATOR FORMAT 3 PER HOPPER (STANDARD)

AERATOR TYPE BT! SPIN FLOW AERATION KIT W/ WEAR

PLATES AND 2 IN. BTI BLACKMAXX INDIVIDUAL AERATION CONTROLS AT

EACH HOPPER

AERATION LOCATION DRIVER SIDE

AERATOR LINE CONTROL 3" BTI BLACKMAX BUTTERFLY VALVE

AERATOR SEAT WHITE RUBBER (FOOD GRADE) SEAT

AERATOR DISK ALLOMAXX DISC

AERATOR HANDLE TYPE ALUMINUM

AERATOR HANDLE POSITION MANUAL 10 - POSITION

AIR INLET

AIR INLET SIZE 3 IN. SCH. 10 ALUMINUM PIPE

AIR INLET LOCATION CHECK VALVES

DRIVER SIDE

(2) BTI OPTIMA CHECK VALVES - (1) AT AIR INLET & (1) UP STREAM OF FRONT

HOPPER DISCHARGE

PROP / PRES CONTROL VALVE

CONTROL VALVE HOUSING

3" BTI BLACKMAX BUTTERFLY VALVE

CONTROL VALVE DISK

ALLOMAXX DISC

CONTROL VALVE HANDLE TYPE

ALUMINUM

CONTROL VALVE HANDLE POSITION

MANUAL 10 - POSITION

BLOW DOWN LINE

BLOW DOWN LINE HOUSING

3" BTI BLACKMAX BUTTERFLY VALVE

BLOW DOWN LINE DISK

ALLOMAXX DISC

BLOW DOWN LINE SEAT

WHITE RUBBER (FOOD GRADE) SEAT

BLOW DOWN LINE HANDLE TYPE

ALUMINUM DRIVER SIDE FRONT

BLOW DOWN LINE LOCATION BLOW DOWN LINE HANDLE POSITION

MANUAL 10 - POSITION

BLOW DOWN RELIEF PRESSURE

15 P.S.I.

TOP AIR

TOP AIR VALVE HOUSING

NONE

TOP LINE LOCATION

NONE

PRODUCT & DISCHARGE

PRODUCT / DISCHARGE LINE SIZE

4 IN

PRODUCT / DISCHARGE LINE MATERIAL

ALUMINUM

PRODUCT / LINE MATERIAL GAUGE

SCHD.40 5" BTI BLACKMAXX BUTTERFLY VALVES

PRODUCT VALVE SIZE PRODUCT VALVE SEAT

WHITE RUBBER (FOOD GRADE) SEAT

PRODUCT VALVE DISK

ALLOMAXX DISC

PRODUCT LINE CONNECTION

GROOVE TO GROOVE CLAMPS AT

FRONT AND REAR

ALUMINUM

CLAMPS

WORM GEAR CLAMPS W/ RUBBER

SLEEVES BETWEEN HOPPERS

PRODUCT VALVE HANDLE TYPE

PRODUCT VALVE HANDLE POSITION

MANUAL 5 - POSITION

PRODUCT TEE TYPE

5 X 4 ALUMINUM STRAIGHT TEE

REAR DISCHARGE LOCATION

EXTEND OVER AXLES TO REAR

NO. OF GAUGE ENCLOSURE

GAUGE LOCATION

Driver Side -Rear- Forward of Tandem

PRIMARY AXLES

MODEL

TANDEM 2

NO. OF PRIMARY AXLES

HEND. INTRAAX AANT 230 - TP SPINDLE

SUSPENSION AXLES

71.5" AXLES

77.5 WIDE AXLES

LIFT KIT_

NONE

WHEEL END PACKAGE

YES

BRAKES

DISC BRAKES - HEND. MAXX22T ADI HUE

(23,000 LB ONLY)

CAM GUARDS HUB AND DRUM NONE, DISC BRAKES

NONE, DISC BRAKES

TIRES

GENERAL RA 11R 22.5 16 PLY

WHEELS

ALUMINUM HP 22.5X8.25 - ALL POLISHED

PRIMARY AXLE TIRE INFLATION SYSTEM

(XP) NONE

CHASSIS

5TH WHEEL PLATE

5TH WHEEL PLATE HEIGHT

GALVANIZED STEEL, ADJUSTABLE

48 IN, HIGH

SUSPENSION CONTROL AUTOMATIC DUMP ON EMERGENCY

GLADHAND

SCALE SYSTEM LOAD GAUGE - DRIVER SIDE REAR

ABS (1) 4S2M MERITOR / WABCO
SLACKS NONE, DISC BRAKES

HUBODOMETER_ NONE

AXLE LUBRICATION HXL-5 CHEVRON-DELO SEMI-FLUID

GREASE W/ SOLID HUBCAPS (H.L.S.

WHEEL END PACKAGE)

DOLLIES - LANDING GEAR - LANDING LEGS JOST - 5 YEAR NO LUBE- D.S.

AIR TANKS ALUMINUM TANK

LIGHT TYPE GROTE L.E.D. W/ GROMMET

REAR I.D. LIGHTS (3) I.D. LIGHTS TOP

LIGHT PANEL (TURN) (STOP) (STOP) - (STOP) (STOP)

(TURN)

STD. MARKER LIGHTS 2 EACH SIDE FRONT & REAR MID-TURNS (1 PAIR) LED-BOXED IN

BACK-UP LIGHTS

AUXILIARY CABLE

NO. OF WORK LIGHTS

WORK LIGHT MODEL

WORK LIGHT LOCATION

WORK LIGHT SWITCH LOCATION

NONE

PAINT

SUSPENSION COLOR MAC BLACK
MAC MACHINE FINISH LOGOS BLACK (931716)

ACCESSORIES
TOE RAIL FULL LENGTH ON BOTH SIDES

CABINET NONE

CENTER WALKWAY ADHESIVE BACKED, SKID-RESISTANT

TAPE BETWEEN TOE RAILS

HOSE STORAGE TUBE (1) 8 IN. X 21 FT. MOUNTED ON CS

GAUGES 1 - LINE P.S.I. / 1 TANK P.S.I. - (INSIDE

ILLUMINATED ENCLOSURE)

MUD FLAPS ANTI-SAIL FLAPS (REAR OF FRONT

FENDERS AND REAR OF BACK FENDERS

PRODUCT DISCHARGE HOSE NONE

FENDERS_ ALUMINUM ROLLED EDGE - SINGLE

CONTOUR AT FRONT, DOUBLE CONTOU!

AT REAR

DOCUMENT HOLDER LOCATED DRIVER SIDE NEAR LANDING

GEAR

AIR INLET ACCESSORIES PTO HOSE HOLDER, MAST, HOOK AND

DUMMY ADAPTER LOCATED DRIVER SID

ABOVE FRONT FENDER