



Hale Trailer Brake & Wheel

A002375-A002380

VIN: 036452-036457



"78721A TK85EFX-5L

O9999-01-Add

Custom Option 1

Custom Option 1

0110140-ADB-14-...

Item #	Category	Description	Weight (lbs)	Qty
78721 A	Custom Options	<p>"78721A TK85EFX-5L</p> <p>85,000-lb. capacity</p> <p>Overall length – 52'-11" closed</p> <p>Max open 191'-1" plus 19' non load bearing pullout at rear.</p> <p>102'" wide</p> <p>12'-7" gooseneck , 112" swing clearance</p> <p>19'" kingpin setting</p> <p>49" 5th wheel height</p> <p>Detachable Gooseneck</p> <p>58" front platform height (102" wide, 24" long)</p> <p>(1) Slide-able rear platform (102'" wide, 36" long)</p> <p>Heavy duty front pullout/rotate down stabilizing legs</p> <p>2-speed landing gear @ rear of gooseneck</p> <p>Narrow Mono-beam design with 5 stages"</p>	39,259	

78721 A	Custom Options	"Kingpin steering 19 ft. non-loadbearing pull-out rear extension Hydraulic lifting leg Tritronic remote control with auto align function Remote can be used wireless or cord type Approximately 42 deg max steer angle (3rd axle) Self-contained hydraulics 13 HP Honda SCU unit in aluminum box with removable cover 3 axle-72" axle spacing 4S2M Anti-lock brakes Steel hub-piloted - cast drums"
78721 A	Custom Options	Red & white conspicuity markings Blasted prior to paint Color: Trail King 2-part polyurethane Air ride suspension 72" axle spacing 25,000 lbs axles (5/8" wall) Machined aluminum wheels inside/outside 235/75R x 17.5 Tires Aluminum Air Tanks 3 tail light package, Super Nova LED STT lights One pair 4" round amber LED strobes at rear (4 lights per side) Micro Nova LED Clearance Lights 1 Pair Mid-Turn LED lights on 5th stage beam." www.
76632	Hydraulics & Controls - Special	76632 EFX - Isolate the accelerator for use when manual steering
08009	Paint	Epoxy primer
08024	Paint	S7203 Black with white decals
74028	Custom Options	74028 TK85EFX - Add plastic fenders ILO standard
78702	Custom Options	78702 TK85EFX - sliding load bunk to be 48" wide ILO std 36"
74027	Custom Options	74027 TK85EFX - Move axles to the rear (SCU in front of the axles)
08569	Miscellaneous	DOT Inspection
15254	Wheels (inside)	6.75 x 17.5 8-hole polished (XP) aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole machined (SP) aluminum wheel

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.