



Hale Trailer Brake & Wheel

A002381-A002383

"78721A TK85EFX-5L

O9999-01-Add

Custom Option 1

Custom Option 1

0110140-ADB-14-...

Item #	Category	Description	Weight (lbs)	Qty
78721A	Custom Options	"78721A TK85EFX-5L 85,000-lb. capacity Overall length – 52'-11" closed Max open 191'-1" plus 19' non load bearing pullout at rear. 102" wide 12'-7" gooseneck , 112" swing clearance 19" kingpin setting 49" 5th wheel height Detachable Gooseneck 58" front platform height (102" wide, 24" long) (1) Slide-able rear platform (102" wide, 36" long) Heavy duty front pullout/rotate down stabilizing legs 2-speed landing gear @ rear of gooseneck Narrow Mono-beam design with 5 stages"	39,259	
78721A	Custom Options	"Kingpin steering 19 ft. non-loadbearing pull-out rear extension Hydraulic lifting leg Tritronic remote control with auto align function Remote can be used wireless or cord type Approximately 42 deg max steer angle (3rd axle) Self-contained hydraulics 13 HP Honda SCU unit in aluminum box with removable cover 3 axle-72" axle spacing 4S2M Anti-lock brakes Steel hub-piloted - cast drums"		
78721A	Custom Options	"Red & white conspicuity markings Blasted prior to paint Color: Trail King 2-part polyurethane Air ride suspension 72" axle spacing 25,000 lbs axles (5/8" wall) Machined aluminum wheels inside/outside 235/75R x 17.5 Tires Aluminum Air Tanks 3 tail light package, Super Nova LED STT lights One pair 4" round amber LED strobes at rear (4 lights per side) Micro Nova LED Clearance Lights 1 Pair Mid-Turn LED lights on 5th stage beam."		
76632	Hydraulics & Controls - Special	76632 EFX - Isolate the accelerator for use when manual steering		
08009	Paint	Epoxy primer		
74028	Custom Options	74028 TK85EFX - Add plastic fenders ILO standard		

08024	Paint	S7203 Black with white decals	
78702	Custom Options	78702 TK85EFX - sliding load bunk to be 48" wide ILO std 36"	
74027	Custom Options	74027 TK85EFX - Move axles to the rear (SCU in front of the axles)	
15004	Custom Options	15004 6.75 x 17.5 8-hole polished (XP) aluminum wheel outside (per heel) ILO Std	6

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.