



Hale Trailer Brake & Wheel A002637-A002645



components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 48' - Base Weight 10,380#
OVERALL WIDTH 8' 6"
KING PIN SETTING 30" - Tapered Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
FRONT SKIRT Aluminum Front and Corners
REAR SKIRT Aluminum
BULKHEAD None
MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)
SIDE RAILS 6" - Alum- Extruded W/Double L Track
FLOOR SILLS 4" Aluminum I - Beam - 10" O.C. Pkg.
Aluminum Sils On 10" Centers.
COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sils-Ctr On Trailer
FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards
WINCH TRACK Double L Aluminum- Extruded Siderail R/S Only
TIE BAR Curb Side - Full Length - 3/8" x 2"
WINCHES 12 Zinc Coated
STRAPS None
LANDING GEAR Two Speed - Jost A500
Extra Brace Forward of Landing Gear With Standard Brace To The Rear of Leg.
SUSPENSIONS Air Ride- Hendrickson - Intraax - 46K -Tandem Slider (AK880)
SUSPENSION LOCATION Slider/Variable
AXLES (2) 22.5K Capacity- Type 30 Chambers- Auto Slacks
AXLE SPACING 49" (+35#)
LIFT AXLE None
DUMP VALVE Auto Dump All Axles Glandhand Activated AK54
Auto Dump All Axles.
SCALES None
ABS SYSTEM Wabco ABS System 2S/1M

PARKING BRAKES All Axles
DUST SHEILDS None
TIRE INFLATION SYSTEM None
TIRES 11R 22.5- DOUBLE COIN
WHEELS Disc - Hub Piloted - 22.5 Steel
ANTI-SAIL MUD FLAPS Behind Rear Axle
STAKE POCKETS 24" O.C. Sides & 5 Across Rear
RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape
SPOOL Triangular Shaped
DOCK BUMPERS Rubber Inboard
CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
CUSTOM LIGHTS None
LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.