

## Hale Trailer Brake & Wheel A002646-A002661



Base Model: FC48X102 Air Slider Steel Sills components description CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span) OVERALL LENGTH 48' - Base Weight 10,380# **OVERALL WIDTH 8' 6"** KING PIN SETTING 30" - Tapered Front **UPPER COUPLER PLATE 1/4" UPPER COUPLER HEIGHT 48"** FRONT SKIRT Aluminum Front and Corners REAR SKIRT Aluminum **BULKHEAD None** MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg) SIDE RAILS 6" - Alum- Extruded W/Double L Track FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg. COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards WINCH TRACK Double L Aluminum- Extruded Siderail R/S Only TIE BAR Curb Side - Full Length - 3/8" x 2" WINCHES 12 Zinc Coated STRAPS None LANDING GEAR Two Speed - Jost A500 \*\*Extra Brace Forward of Landing Gear With Standard Brace To The Rear of Leg.\*\* SUSPENSIONS Air Ride- Hendrickson - Intraax - 46K - Tandem Slider (AK880) SUSPENSION LOCATION Slider/Variable AXLES (2) 22.5K Capacity- Type 30 Chambers- Auto Slacks AXLE SPACING 49" (+35#) LIFT AXLE None DUMP VALVE Auto Dump All Axles Glandhand Activated AK54 \*\*Auto Dump All Axles.\*\* SCALES None ABS SYSTEM Wabco ABS System 2S/1M PARKING BRAKES All Axles **DUST SHEILDS None** TIRE INFLATION SYSTEM None TIRES 11R 22.5- DOUBLE COIN WHEELS Disc - Hub Piloted - 22.5 Steel ANTI-SAIL MUD FLAPS Behind Rear Axle STAKE POCKETS 24" O.C. Sides & 5 Across Rear RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape SPOOL Triangular Shaped DOCK BUMPERS Rubber Inboard CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced **TOOLBOX MATERIAL None TOOLBOX TYPE None TOOLBOX LOCATION None CUSTOM LIGHTS None** LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted