



Hale Trailer Brake & Wheel

A002934-A002958

VIN: 48029-48053

A002970-A002994

VIN: 48054-48078



Infinity Flat 48 Air Slider (HAICF12SAT)

Detailed Specifications		General	
Model	HAICF12SAT		
Length x Width	48 feet x 102 inches		
Suspension	Sliding Air Tandem		
Frame Rating	80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads		
Kingpin Setting	30 inches		
Fifth Wheel Height	49 inches		
Axle Spread	49 inches		
VIN Plate	Bilingual US/Canadian VIN plate		
Estimated Weight	Est. Weight: 10950 lbs. +/-3%		
Structural			
Main Beams	130K Load Bearing Flanges		
Crossmembers	12 inch Centers - 4 inch Jr. I-Steel		
Single Coil Hauling Package	Included		
Knee Braces	Fabricated on Approx. 60 inch C/C		
Side Rails	Exclusive Revolutionary RASR Rail Technology - One Piece Routed Aluminum Designed for Strength and Impact		
Stake Pockets	Routed Aluminum on 24-inch Centers (2 Load Securement Openings in Between Stake Pockets)		
Rubrail	Integrated with Side Rail		
Front Corners	Tapered Steel		
Bumper	Weld-On; Meets U.S. Underride Requirements - Painted Steel		
Winch Track	Full-Length Integrated Double L Type Aluminum on Both Sides		
Chain Cargo Tie Downs	15 Pair - Recessed in Siderails		
Bulkhead Pockets	4 - DOT Type Bulkhead Pockets Only - Welded to Front		
Landing Gear			
Landing Gear	Jost A400G19 Steel Landing Gear with Forward and Rear Bracing		
Flooring			
Flooring	1 1/8 inch Aluminum with 4 Apitong Wood Nailer Strips		
Suspension			
Suspension Detail	Hendrickson AAZNT46K Intraax Air Ride Slider - 60 inches Adjustable		
Number of Axles	2		
Axle Spindle	Tapered		
Brakes	Spring Brakes, Auto Slacks		
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums		
Wheel Ends	Grease in Hubs - *** 5-Year Wheel End Warranty ***		
Tire Inflation System	None Standard		
Air Lift	None Standard		
Wheels and Tires			
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD		
Tires	11R 22.5 14PR OEM Standard tires		



Detailed Specifications

Air System	
Air Line Filters	(2) Meritor In-line Type Installed
ABS	4S/2M - No Cable or Tool
Full System Dump	Auto Glad Hand Dump Installed
Control Box	Standard Mount of Controls on Slider Frame
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer
Electrical System	
Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side
Paint and Decal	
Paint	Black Urethane on Steel Parts with Infinity Decals
Conspicuity Tape	Per NHTSA Specs - Installed in Recess on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed
Miscellaneous	
Mudflaps	1 Set OEM Standard
Sliding Winches	12 standard: Sliding Rope Hook/Winch Strap Hook Retainers
Winch Location	Equal Both Sides
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Sliding J-Hook for Strap with Ring	None Standard
Registration Holder	Install Registration Holder - OEM Standard
Options	
Bulkhead	Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high
Spare Tire Carrier	None Standard
Hubodometer	None Standard
Tool Box	None Standard
Literature	
Trailer Literature	Infinity Brochure

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.