

HALE

TRAILER

BRAKE & WHEEL

Hale Trailer Brake & Wheel

A003146-A003147



CHIPPER

Cubic Yards 105

Weight 14714 lbs. ***

BODY

LOAD PROFILE	MATERIAL, 80K GVWR
LENGTH	45
WIDTH	102
DRIVE UNIT	KEITH, 25 SLAT 3-1/2 IN. CYLINDER (HEAVY DUTY)
FLOOR	KEITH 2190 (1975), 7/32 IN. (102 W)
ADD 24 INCH WEAR STRIPS TO END OF SLATS	
HYDRAULIC PIPE	STAINLESS STEEL HYDRAULIC PIPE
CROSSMEMBER TYPE	HEAVY FULL
CROSSMEMBER SPACING	5-1/4 IN. I-BEAMS, 12 O.C.
RUBBER SEAL	NONE
WALL HEIGHT	92
FRONT WALL THICKNESS	.062
ALL PREPAINTED WHITE PANELS	
MID WALL THICKNESS	.062
REAR WALL THICKNESS	.062
LAST SHEET AT REAR TO BE .125" THICKNESS	
FULL LID	NONE
TOP RAIL OPTION	STD TOP RAIL
STD TOP RAIL	
UPRIGHT SPACING	14 IN.
12" UPRIGHT SPACING	
ADDITIONAL UPRIGHTS AT FRONT	NO
BULKHEAD	.165
BULKHEAD STEPS	LADDER ONLY
FRONT FENDERS WITH FLAPS	NONE
BOTTOM RAIL	SQUARE NO CLEAN OUT
UPPER CROSS TUBES / ARCH	6
USE ONLY 3 CROSS TUBES BETWEEN FRONT AND REAR CAPS	
FRONT CAP	YES
REAR CAP	NO
TIRE CARRIER	(1) IN MIDDLE ONLY

LIGHTS

LIGHT TYPE	GROTE L.E.D. W/ GROMMET
LIGHT PANEL	3 LARGE-3 SMALL-3 LARGE (SPLIT LIGHT PANEL) 000 000 000
APRON	NONE
STD. MARKER LIGHTS	(5) EACH SIDE
	(5) PER SIDE TOP & BOTTOM
MID-TURNS	(1) PAIR L.E.D. (COMBO)
BACK-UP LIGHTS	(1) PAIR L.E.D. BACK UP LIGHTS
	ADD ONE PAIR OF WORKLIGHTS TO INSIDE FRONT. WIRE TO FRONT IN WATERPROOF SWITCH
AUXILIARY CABLE	NONE
REAR POCKET LIGHTS	(1) PAIR

GATE	
GATE OPERATION	BI-FOLD
	QUAD LOCKS
GATE OPTIONS	SOLID .080
	WHITE DURAPLATE
HINGE TYPE	BARN DOORS SIDE SWING (ALUM.)
SAFETY CHAIN	YES
WINDERS / SAFETY LATCH	NONE
GATE STEPS	NONE
TARP HOOKS	NONE

PRIMARY AXLES	
MODEL	CLOSED TANDEM
NO. OF PRIMARY AXLES	2
SUSPENSION	MAC FABBED GALVANIZED SINGLE LEAF TAN. (49)
AXLE SPACING	49
SUB-FRAME	TANDEM, HI-TENSILE FAB (SPRING RIDE ONLY)
	USE HENDRICKSON VANTRAAX AIR RIDE SLIDER ASSEMBLY
AXLES	77.5 IN. 5/8 IN. AXN TP W/ 25K
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
CAM GUARDS	NONE
HUB AND DRUM	CAST W/ STEEL HUB HP 10 STUD TP, LS, 7 IN.
TIRES	GENERAL RA 11R 22.5 16 PLY
WHEELS	A & S HP 22.5X8.25 - INSIDE STEEL, OUTSIDE POLISHED (XP)

LIFT AXLES	
NO. OF LIFT AXLES	0
LIFT AXLE SUSPENSION	NONE
LIFT KIT	NONE
LIFT AXLE DISTANCE	N/A
LIFT AXLE	NONE
LIFT AXLE BRAKES	NONE
LIFT AXLE CAM GUARDS	NONE
LIFT AXLE HUB AND DRUM	NONE
LIFT AXLE TIRES	NONE
LIFT AXLE WHEELS	NONE
LIFT AXLE CONTROLS	NONE
FREE WHEEL VALVE	NONE

STEERABLE LIFT AXLES	
NO. OF STEERABLE AXLES	0
STEERABLE AXLE SUSPENSION	NONE
STEERABLE AXLE LIFT KIT	NONE
STEERABLE AXLE DISTANCE	N/A
STEERABLE AXLES	NONE
STEERABLE AXLE BRAKES	NONE

STEERABLE AXLE HUB AND DRUMS	NONE
STEERABLE AXLE TIRES	NONE
STEERABLE AXLE WHEELS	NONE
STEERABLE AXLE CONTROLS	NONE

CHASSIS

PIN SETTING	36
5TH WHEEL PLATE	3/8 LOW PROFILE
5TH WHEEL PLATE HEIGHT	48 IN. HIGH
GALVANIZED SUSPENSION HANGERS	INCLUDED W/ SUSPENSION
SUSPENSION CONTROL	NONE
ABS	(1) 2S1M MERITOR / WABCO
SLACKS	AUTOMATIC
TIRE INFLATION SYSTEM	NONE
AXLE LUBRICATION	5 YR. SYNTHETIC GREASE
HUBODOMETER	NONE
DUST COVERS	NONE
DOLLIES - LANDING GEAR - LANDING LEGS	JOST A451 - (62,500 LB.) - 10 YEAR NO LUBE - STEEL - (REVERSE MOUNT) D.S.
REGISTRATION HOLDER	BETTS PS-1 W/ SIGHT GLASS (ROUND HOLDER)
AIR GAUGE / SYSTEM	YES, IN FRONT
ENCLOSURE FOR SWITCHES	NONE
AIR TANKS	12 IN. ALUMINUM TANK
HYDRAULIC HOSE FITTING	1 IN. X 108 IN. HOSE W/ WING FITTING
FLAPS FRONT OF TIRES	NONE
FLAPS REAR OF TIRES	FLAP BEHIND REAR AXLE
BUMPER	D.O.T. BUMPER

TARP

TARP MANUFACTURER	AERO KWIK LOCK - VINYL
TARP CONTROL	MANUAL
TARP COLOR	BLACK
TARP BRACKET	NONE

PAINT

SUSPENSION COLOR	BLACK SOFT COAT
PIN STRIPING	BLACK (931716)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.