



## Hale Trailer Brake & Wheel A003178-A003183



Base Model #: LB35-38CS

components description

CAPACITY 35 Ton

OVERALL LENGTH 45'

OVERALL WIDTH 8' 6"

DECK LENGTH 27'

DECK HEIGHT 38" - Loaded

DECK FLOORING Apitong - 1 1/2" - Covering Entire Deck

MAINBEAMS 16" Fabricated I-Beam - Positive Camber

SIDE RAILS 12" Fabricated I-Beams - Positive Camber

GOOSENECK Flat Deck Wood w/ 21 Degree Slope - Steel & Traction Bars

KING PIN SETTING 18"

KING PIN PLATE 5/16 Plate

KING PIN SWING RADIUS 84"

KING PIN HEIGHT 48"

DOVETAIL 4' Steel w/ Traction Bars

WHEEL WELL Covered w/ Steel Plate & Traction Bars

LOADING RAMP Spring Assisted - 72" x 24" - Self Cleaning

LANDING GEAR Two Speed - 50,000 lbs.

D RING 16

TOOL BOX IN GOOSENECK Tool Box in Gooseneck

AXLE (2) 25,000 lb. Capacity w/ 49" Axle Spacings, Auto Slack, ABS

SUSPENSION Hutchens - 3 Point, 4 SPRING - 56,000 lb Capacity

WHEELS Disc - Hub Piloted

TIRES 255/70R22.5

PARKING BRAKES Type 30/30 Spring Brakes - 2 Axle

WIRING D.O.T Sealed Wiring Harness

LIGHTS LED Pkg - Sealed Lights Rubber Mounted

PAINT PPG Black - Epoxy Primer and Acrylic Polyurethane - Shot Blasted

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.