



Hale Trailer Brake & Wheel  
A003605-A003640  
VIN: 211376-211391



ITEM	DESCRIPTION
<b>TYPE</b> <b>APPLICATION</b>	SEMI-TRAILER, STEEL PLATFORM LEGEND SD GALVANIZED SEE SECTION
<b>DIMENSIONS</b> <b>LENGTH</b> <b>WIDTH</b> <b>HEIGHT</b>	48'-0" 102", 97" between side rails. Floor, approximately 59 1/2" high at front and 54" at rear.
<b>COUPLING</b> <b>COUPLER PLATE</b> <b>KING PIN LOCATION</b> <b>COUPLER HEIGHT</b>	1/4", 80 000 psi steel, plug welded structure. 30" from front. 48".
<b>STRUCTURE</b> <b>FLANGES</b> <b>WEB</b>  <b>GOOSENECK</b> <b>CROSSMEMBERS</b> <b>FLOOR</b> <b>FLOOR FASTENING</b> <b>SIDE RAILS</b> <b>SIDE BOXES</b>  <b>RUB RAILS</b> <b>CORNERS</b> <b>X BRACES</b>	44" c/c frame with "CAMBER". 3/8" x 5", high tensile. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer. 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. Aptitong or equivalent, 1 1/8" thick shiplap finished, no preservative. Screws 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets. 3/8" x 2 1/2" shaped steel. Bevelled. Between main beams, full length.
<b>ENDS</b> <b>FRONT RAIL</b> <b>BUMPER</b>  <b>HEADBOARD</b>  <b>POCKETS</b> <b>BUMPER</b> <b>REAR RAIL</b>	Formed steel, bolted. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. *** Galvanized *** 2 bolted galvanised pockets at front for removable headboard. 2 rubber dock, at the end of rear rail. Formed steel.
<b>ELECTRICAL</b> <b>FRONT CONNECTOR</b> <b>ELECTRICAL SYSTEM</b> <b>MAIN SYSTEM</b>  <b>FLASHERS</b>	7 way (SAE J560). Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.



ITEM	DESCRIPTION
<b>LANDING GEAR</b>	Holland, Mark V (LGS-4F315), with mounting plate & solid axles. *** Galvanized ***
<b>SAND SHOES</b>	10" x 11 1/2"
<b>CRANK</b>	Road side.
<b>BOGIE</b>	
<b>BASIC MECHANICAL</b>	
<b>BOGIE</b>	Slider, Hutch H-9000, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 6" c/c between locating holes, (48" travel).
<b>MECHANICAL (GROUND AXLES)</b>	
<b>SUSPENSION</b>	Hutch H-9700, tandem, under mount, 49" spread.
<b>U-BOLTS</b>	With nuts at bottom.
<b>SPRINGS</b>	3 leaves, model TRA 2741, 12 000 lbs capacity.
<b>AXLE(S)</b>	Meritor, TN 467_L, 22 500 lbs. capacity.
<b>CAM SHAFTS</b>	28 splines.
<b>TRACK</b>	77 1/2".
<b>DUST SHIELDS</b>	None (Meritor axles).
<b>BRAKES</b>	16 1/2" standard, FRAS-LE MA212Q+ extended life lining.
<b>BEARINGS</b>	HM 218248 and HM 212049
<b>SLACK ADJUSTERS</b>	Meritor, automatic, 28 splines.
<b>SEALS</b>	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
<b>BRAKE CHAMBERS</b>	T.S.E. brake, "Omnibrake" (30-30). (4 years warranty by T.S.E. for parts only).
<b>HUBS AND DRUMS</b>	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
<b>RIMS</b>	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
<b>TIRES</b>	General, 11 R 22.5 HT                      14 ply    (41.1")
<b>AIR SYSTEM</b>	
<b>GLAD HANDS</b>	Fixed.
<b>AIR VALVES</b>	Meritor Wabco, ABS, 2 sensors 1 modulator.
<b>ACCESSORIES</b>	
<b>REGISTRATION HOLDER</b>	One plastic, Betts-PS-1 or equivalent.
<b>MUD FLAPS</b>	One set, rubber with moose logo and vertical grooves to reduce spray.
<b>SLIDING TRACK</b>	Full length, "LL" extruded aluminum, road side.
<b>WINCHES</b>	Qty: 12, KINEDYNE #1020ZP, zinc plated slider (low profil 5 7/8").
<b>REMARK</b>	*** Vin plate to be made of metal. Pre-drill the web prior to galvanizing ***
<b>FINISHING</b>	
<b>PAINT</b>	Ready for Galvanized plateform.
<b>BOGIE</b>	One coat of epoxy primer and one acrylic urethane top coats, Color: Grey métalllic, code: PPG Q37-939514. Axles (wheel end) included. (Tandem).
<b>RETROREFLECTIVE TAPES</b>	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
<b>WHEELS OR RIMS</b>	White (power top coat).



ITEM	DESCRIPTION
<b>REMARK</b>	*** Vin plate to be made of metal. Pre-drill the web prior to galvanizing ***
<b>GALVANIZED CHOICES</b> <b>PLATFORM</b>  <b>CROSSMEMBERS</b> <b>FRONT RAIL</b> <b>SIDE RAIL</b> <b>REAR RAIL</b> <b>BUMPER</b>	Galvanized choices. Galvanized platform. (no paint) ** WARNING: holes parachute shaped required for dripping ** Galvanized Galvanized Galvanized Galvanized Galvanized
<b>CONFORMITY</b>	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.