



Hale Trailer Brake & Wheel
A003793-A003813
VIN: 49282-49302



Velocity Flat 48 Spring Slider (HAVSF12SST)

Detailed Specifications		General	
Model	HAVSF12SST		
Length x Width	48 feet x 102 inches		
Suspension	Sliding Spring Tandem		
Frame Rating	80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads		
Kingpin Setting	30 inches		
Fifth Wheel Height	49 inches		
Axle Spread	49 inches		
VIN Plate	Bilingual US/Canadian VIN plate		
Estimated Weight	Est. Weight: 12210 lbs. +/-3%		
Structural			
Main Beams	130K Load Bearing Flanges		
Crossmembers	12 inch Centers - 4 inch Jr. I-Steel		
Knee Braces	Fabricated on Approx. 60 inch C/C		
Side Rails	6 inch Structural Channel @ 6.5 lbs/ft		
Stake Pockets	3/16 inch Steel on 24 inch Centers		
Pipe Spools	Double Between Stake Pockets		
Rubrail	3/8 inch x 2 1/2 inch Steel		
Front Corners	Tapered		
Bumper	Weld-On; Meets U.S. Underride Requirements		
Winch Track	Steel on Road Side		
Bulkhead Pockets	4 - F-5 DOT-Type Steel		
Landing Gear			
Landing Gear	Jost A400G19 Steel Landing Gear with Forward and Rear Bracing		
Flooring			
Flooring	1 1/8 inch Apitong Wood		
Suspension			
Suspension Detail	OEM Standard 3-leaf spring slider - 60 inches adjustable		
Number of Axles	2		
Axle Spindle	Tapered		
Brakes	Spring Brakes, Auto Slacks		
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums		
Wheel Ends	Oil in Hubs		
Tire Inflation System	None Standard		
Wheels and Tires			
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD		
Tires	11R 22.5 14PR OEM Standard tires		
Air System			
Air Line Filters	(2) Meritor In-line Type Installed		
ABS	4S/2M - No Cable or Tool		
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer		



Detailed Specifications

Electrical System	
Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side
Paint and Decal	
Paint	Black Urethane with Velocity Decals
Conspicuity Tape	Per NHTSA Specs - Installed on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed
Miscellaneous	
Mudflaps	1 Set OEM Standard
Sliding Winches	12 standard
Winch Location	All Road Side
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Registration Holder	Install Registration Holder - OEM Standard
Options	
Bulkhead	Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high
Spare Tire Carrier	None Standard
Hubodometer	None Standard
Tool Box	None Standard
Literature	
Trailer Literature	Velocity Brochure

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.