

## Hale Trailer Brake & Wheel A004306-A004308

VIN: 33584-33586



Base Model: DF48x102 3 Axle 60 Ton 275 Extreme Duty

Serial #: 33584 -33586 components description

CAPACITY Heavy Duty Package - 120,000 lbs. GVWR (110K Eq. Dist. in 10' & 70,000 in 4' Span)

\*\*Extreme Duty.\*\*

OVERALL LENGTH 48' UPPER DECK LENGTH 12'

\* \* \* Minimum Pitch of 2-3/4" \* \* \*

LOWER DECK LENGTH 36' (Deck Height-42")

**OVERALL WIDTH 8'6"** 

KING PIN SETTING 18"

**UPPER COUPLER PLATE 5/16"** 

UPPER COUPLER HEIGHT \* \* 50" \* \*

**BULKHEAD None** 

MAINFRAME 26" Fabricated - PreCambered I-Beams - Heavy Duty

\* \* Main Beams 1/2" X 6" Top Flange, 3/4" x 6" Bottom, 1/4" Webs Throughout, Lower Deck, 1/4 Rear Section, 1/4" Web in Neck. \* \*

\* \* Transition Plate \* \*

\* \* 1/4" Diamond Plate Over Wheels. \* \*

\* \* \* 1/4" Diagonal Bracing, Main Beam to Outer Rail. \* \* \*

\* \* \* \* Rear of Trailer Prep for 4th Flip Axle. \* \* \* \*

SIDE RAILS 8" Heavy Duty

FLOOR SILLS 6" I-Beam 12/12/12 O.C. HD Pkg. Drop Frame

\* \* Approx. 6 Aux. Crossmembers over Suspension at Middle of Trailer, and in Gooseneck. \* \*

\* \* Install Sub Sills in High Stress Areas. \* 3

FLOOR DECKING \* \* 1-1/2" Apitong \* \*

WINCH TRACK Steel Slide Entire Length of Drivers Side

WINCHES 12 Zinc Coated

STRAPS None

LANDING GEAR Two Speed

SUSPENSIONS (Hendrickson)- 30K Suspension W/ (30K) Lift Rear Axle

\*\*9" Ride Height.\*\*

LIFT AXLE Lift Rear Axle



DUMP VALVE Dump Valve in Box Includes: Manual Override, Liquid Filled Gauges and Lift Axles

\*\* All Air Control valve in Box.\*\*

SCALES None

AXLES (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride(Parallel Spindle)

\*\*Parallel Spindle.\*\*

\*\*23K Brake Linings.\*\*

AXLE SPACING 61" Wide Spread

PARKING BRAKES 3 Axle

**DUST SHEILDS None** 

WHEELS Disc - Hub Piloted - Steel Inside and Polished Aluminum Outer

\* \* \* \* Steel Inside, Polished Outside w/ Wheel Pads Between Wheels \* \* \* \*

TIRES 275/70R 22.5 - 42" Loaded Deck Height

ANTI-SAIL MUD FLAPS Rear Frame

STAKE POCKETS 4" Deep - 24" O.C. - Sides Only

RUB BAND STEEL 3/8" X 3"

PIPE SPOOLS Double

DOCK BUMPERS None

\* \* \* \* Heavy Duty Rear Skirt and Rear End Material \* \* \* \*

\* \* \* Aluminum Sheet on Outside Rear to Cover 3 Light Stop/Tail/Turn \* \* \*

**DOVETAIL None** 

LOADING RAMPS None

TIRE CARRIERS None

**CARGO TIE DOWN None** 

**TOOLBOXES None** 

**TOOLBOX TYPE None** 

LIGHTS Sealed Wiring Harness w/ LED Pkg

\*\*Use Flange Mounted Anti-Theft S/T/T On Rear Skirt, (Due To Skirt Thickness).\*\*

**PAINT Black**