

## Hale Trailer Brake & Wheel A004477-A004524 VIN: 5A0852-5A0899



XTP4880SS2 (Model: XCA4880SSXT848492)	
Detailed Specifications General	
SKU	XCA4880SSXT848492
Capacity	80,000# Distributed - Self-Supporting, Properly Blocked
Length	48 feet 0 inches
Width	8 feet 6 inches
Weight	Est. Configured Weight: 16230# +/- 3%
-	Gooseneck
Kingpin	24 inches
Deck	
Loaded Fifth Wheel Height	49 inches
Landing Gear	OEM Standard
Bulkheads	None
Bulkhead Pockets	4 - F-5 DOT-Type Steel
Main Beams	Minimum Grade 80 Flanges
Crossmembers	12 inch Centers - 4 in Jr I-Steel
Deck Lock	Approx. Every 5 feet
Front Corners	Tapered
Side Rails	6 inch Structural Channel @ 6.5lbs/ft
Stake Pockets	3/16 inch Steel on 24 inch Centers
Pipe Spool	Single Pipe Spool
Rubrail	2 1/2 inch x 3/8 inch Thick HD Mill Formed Steel
Flooring	1 1/8 inch Wood
Winch Track	Full-Length Steel on Roadside
Sliding Winches	12 - without Straps
Winch Straps	None
Air and Electrical at Extension Locks	Inside Track System
Toolbox	None
Bumper	Meets Underride Requirements
Mudflaps	1 Set - Fontaine
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder
	Rear Bridge: Axles
Number of Axles	2
Axle Spread	49 inches
Brakes	Spring Brakes, Auto Slacks
Dust Shield	None
Hub and Drums	10-Hole Hub-Piloted with Outboard Cast Drums
Rear Bridge: Suspension	
Suspension	Sliding Spring Tandem Hutch H-9700 3 Leaf Spring Slider - 96 inch Adjustable CAL LEGAL
ABS	2S/1M - No Cable or Tool
Manual Dump Valve	None
Liquid Filled Gauge	None
Load Scale	None



**Detailed Specifications** 

Wheels and Tires	
22.5 x 8.25 Steel Disc Wheels - Pre-painted White	
11R 22.5 OEM Economical	
None	
None	
Grease in Hubs	
Lighting	
Sealed Harness and LED Lights with 4 inch Flush Mounted Amber Strobes (No Battery Backup)	
3 Lights/Side, 3 Lights/Side on Rear	
Paint	
Fontaine Black Polyurethane Enamel	
Terms	
Price Includes Commodity Surcharges	
Ex Works- Springville, AL, USA	
XTP4880SS2	

XTP4880SS2 Base Model (Note: Options not shown)





