

## Hale Trailer Brake & Wheel A004558-A004572 VIN: 33664-33678



## **BASE MODEL: EF53 | Extendable Flatbed**

components	description
CAPACITY	Heavy Duty Package - 100,000 lbs. GVWR (80,000 in 10' Span Closed)
OVERALL LENGTH	53' - 90' Extendable Trailer
OVERALL WIDTH	8' 6"
KING PIN SETTING	24"
UPPER COUPLER PLATE	1/4"
UPPER COUPLER HEIGHT	48"
BULKHEAD	None
MAINFRAME	26" Fabricated - PreCambered I-Beams
INTER-FRAME COVER	1/8" Smooth Steel Plate
SIDE RAILS	6" - 6.5# Per Foot
FLOOR SILLS	4" Steel I-Beam 12" O.C. STD Pkg Capacity
FLOOR DECKING	1-1/8" Apitong
WINCH TRACK	Steel Slide Entire Length of Drivers Side
WINCHES	12 Zinc Coated
STRAPS	None
LANDING GEAR	Two Speed - Jost A500
SUSPENSIONS	Air Ride - Slider 3 Axle
SUSPENSION LOCATION	Slider/Variable
AXLES	(3) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride
AXLE SPACING	54.5"
LIFT AXLE	None
DUMP VALVE	None
SCALES	None
ABS SYSTEM	Wabco ABS System 4S/2M
PARKING BRAKES	All Axles
DUST SHEILDS	None
WHEELS	Disc-Hub Piloted-22.5 Steel
TIRES	11R 22.5- Double Coin
ANTI-SAIL MUD FLAPS	Behind Rear Axle
STAKE POCKETS	24" O.C. Sides & 4 Across Front, 5 Across Rear
RUB BAND STEEL	3/8" X 2-1/2" Recessed for DOT Tape
PIPE SPOOLS	Double
DOCK BUMPERS	Rubber Inboard
TOOLBOX MATERIAL	None
TOOLBOX TYPE	None
TOOLBOX LOCATION	None
TIRE CARRIERS	None
CUSTOM LIGHTS	None
LIGHTS	Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
PAINT	Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted
CUSTOM 1	None
CUSTOM 2	None
	,

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

DISCLAIMER