



# Hale Trailer Brake & Wheel

## A005021-A005024

### VIN: 078721-078722 & 078730-078731



### GENESIS FRAME DUMP

Length	33	<b>BODY SPECIFICATIONS</b>		Body	
Width	96" INBOARD	Tarp	NONE	Accessories	
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP	Tarp Bows	NONE		
Side Mat'l-front	4' - .100 WALL	Tarp Basket	NONE		
-middle	23' - .140 WALL	Tarp Hooks	NONE		
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16" (10)	<b>TAILGATE</b>	
Side Options	NONE	Bulkhead	D/S-MANDOOK	Height	FULL - GENESIS
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Mat'l Thkness	.140 WALL
		Body Fenders	18"	Slope	NONE
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Hinges	OVERSLUNG
		Inside	NONE	Side Swing	YES -W / GRD CNTRL-P/S HINGE
Floor Options	STUB LONGITUDINALS	Shovel Hgr	D/S-FRAME	Gateseal	RUBBER
				Safety Latch	ONE EACH SIDE
Tailgate Control	AIR / FRAME + ELEC CC (4)	Light Panel	FULL - LED; X=LED B/U LIGHTS	Coal/Grain Door	NONE
Body Pkg	NONE	Options	OOX ooo XOOO (11)	Coal Chute	NONE
Options		Marker Lights	LED - 5 PR TOP & BOTTOM	Gate Options	
Vibrator	NONE	MMTS	BELOW RAIL - LED		
Mudflaps	STD + ACROSS REAR (1)	Apron	NONE		

### CHASSIS SPECIFICATIONS

Model	TRIAXL-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	34'			D/S CRANK	
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-265 (2)(10)			Elec Coupler	7 WAY + ISO 7 WAY LABELED
Chassis Neck	STD	Distance:		AUXILIARY"	
King Pin Setting	18"	From:		Hyd Tank	NONE
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT			Hyd Hose Fitting	WINGNUT
5th Whl Ht	49"	Controls		Hyd Hose Length	108"
Overhang	6"			Tow Hooks	TWO-ONE EACH SIDE
Rear Axle Setting	21.5"	Location		Paint	BLACK SOFTCOAT
K/P To Rear Axle	411.5"	Axle(s)			NONE
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Accessories		Chassis	CHASSIS REAR CM: TAPERED
Susp Control	FRAME + ELEC CC (4)(9)			Options:	W/ DIAMOND PLATE COVER
Susp Spacing	52" - 52" (6)	Brakes			
Susp Options	GALVANIZED HANGERS	Drums			
Springs	AIR	Hubs			
Axles	TP SPINDLES	Wheels			
Accessories	NONE	Tires			
Brakes	16-1/2" x 7"				
Drums	CAST				
Hubs	10 STUD STEEL				
Wheels	8.25 x 24.5 12 HP				
Tires	11R 24.5 RA H 16 PLY GENER.				

### REMARKS: REF E13482

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION.
2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
3. RIGHT WEIGH OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.
4. WIRED TO AUXILIARY ISO 7 WAY PLUG
5. HEIGHT CONTROL VALVE ON AXLE #2.
6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
7. ALL FRAME SWITCHES TO BE AIR IN BOX ON D/S NEAR LANDING GEAR.
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
9. NO CROSSOVER KITS WEIGHT: 14,036
10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.
11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.