

## Hale Trailer Brake &amp; Wheel

A005133-A005141

VIN: 078626-078634



## ALUMINUM "BST" PLATFORM TRAILER

LENGTH:	48'	SUSPENSION:	AAT30K/E3-L (LIFT)E2-E1 (2)(6)
WIDTH:	102"	LOWERING KIT:	MANUAL FRAME SWITCH & ELEC CC (5)
NOSE:	SQUARE NOSE & ISO 7 WAY MARKED AS AUX WIRED TO BOX @ THE REAR	AXLE TO AXLE:	60" - 60"
KING PIN SETTING:	30" W/ 3/8" STEEL- NO ACCESS HOLES	AXLE TO REAR:	30"
FLOOR:	KNURLED 3 NAILERS INTEGRATED SIDE RAIL	LIFT / AXLE:	CENTER AXLE L LIFT (8)
XMEMBER SPACING:	22"	SPACING:	
COIL PACKAGE:	YES (CENTER)-W/ STANDARD CLP PKG	F.W. HEIGHT:	50"
SPOOLS:	DOUBLE	CONTROLS:	FRAME SWITCH <b>W/BRAKE RELEASE</b> + ELEC CC
POCKETS:	HEAVY DUTY	AXLES:	TP
ROPE HOOKS:	NONE	AUTO SLACKS:	STD
TIE DOWNS:	NONE	BRAKES:	HENDRICKSON MAXX 22T DISC BRAKES
MARKER LIGHTS:	LED - 5 PR	ABS SYSTEM:	4S/2M
MID TURN SIGNAL:	YES-COMBO MARKER/MMTS BELOW RAIL	HUBS:	10 STUD LW STEEL W/ HXL-5 WHEEL PACKAGE
FLAT <input checked="" type="radio"/> ANGLED <input type="radio"/>		WHEELS:	8.25 X 24.5 6 HP/ 6 MP
LIGHT PANEL:	LED - 11 LIGHTS (OOOX ooo XOOO) (1) X=LED B.U LIGHTS WIRED TO AUX PLUG FULL WIDTH BUMPER 1/2 STEPS ON REAR	TIRES:	11R 24.5 HSR 2 H 16 PLY CONTINENTALS
BULKHEAD:	NONE	LANDING GEAR:	JOST AX150 D/S CRANK
TYPE:		TIRE CARRIER:	NONE
HEIGHT:		TOOLBOX: QTY:	ONE-3/16" AERO EXTREME CAM LOCK STYLE
RETURNS:		SIZE:	24" X 24" X 60"
MAT'L:		LOCATION:	D/S-JUST AHEAD OF FORWARD AXLE
ACCENT TAPE:	EAST BLACK	MAT'L:	SMOOTH ALUM, DBL DOOR LOW MOUNT FOR WINCH CLEARANCE
PAINT:	EAST BLACK	MUDFLAPS:	STD + LO-MOUNT (3)(4)
WINCH TRACK:	STANDARD INTEGRATED RAIL	TYPE:	BLACK RUBBER
LOCATION:	BOTH SIDES	LOCATION:	REAR
WINCHES:	12 - EA. EXTREME ZINC - D/S		
WINCH CLIPS:			
STRAPS:			

## REMARK REF 74530

- DUNNAGE STORAGE IN LIGHT PANEL FACE W/ DROP DOWN DOOR - 10' LONG - REF 67239.
- GALVANIZED HANGERS - ALL AXLES.
- HIGH MOUNT FLAPS WITH PASS THROUGH** REARWARD OF AXLE #1 AND AXLE #2
- BLACK RUBBER CENTER MUDFLAP AHEAD OF AXLE #1
- SUSPENSION EXHAUST TO BE FRAME SWITCH (LOCATED @ D/S LANDING GEAR) AND ELEC CC WIRED TO AUXILIARY
- MERITOR 10 MPH AUTO REINFLATE ON AXLE #3 (REAR AXLE) AND WIRED TO AUXILIARY **WEIGHT: +/-3%: 11606**
- ALL FRAME SWITCHES TO BE LOCATED IN POLYCARBONATE BOX LOCATED @ D/S LANDING GEAR. **CHANGE 1, 2**
- WIRE LIFT AXLE CONTROLS TO AUX PLUG**

## DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.