



Hale Trailer Brake & Wheel
A005266-A005268
VIN: 065062-065064



CHIPPER

Model # TNSP45FR920-2022

Weight 14842 lbs. * Cubic Yards 100**

BODY

LOAD PROFILE	MATERIAL, 80K GVWR
LENGTH	45
WIDTH	102
DRIVE UNIT	KEITH, 25 SLAT 3-1/2 IN. CYLINDER (HEAVY DUTY)
FLOOR	KEITH 2190 (1975), 7/32 IN. (102 W)
ADD 24 INCH WEAR STRIPS TO END OF SLATS	
HYDRAULIC PIPE	STAINLESS STEEL HYDRAULIC PIPE
CROSSMEMBER TYPE	HEAVY FULL
CROSSMEMBER SPACING	5-1/4 IN. I-BEAMS, 12 O.C.
RUBBER SEAL	NONE
WALL HEIGHT	92
FRONT WALL THICKNESS	.062
ALL BLACK PREPAINTED PANELS	
MID WALL THICKNESS	.062
REAR WALL THICKNESS	.062
LAST SHEET AT REAR TO BE .125" THICKNESS	
FULL LID	NONE
TOP RAIL OPTION	STD TOP RAIL
STD TOP RAIL	
UPRIGHT SPACING	14 IN. 0.0
12" UPRIGHT SPACING 0.5	
ADDITIONAL UPRIGHTS AT FRONT	NO
BULKHEAD	.165
BULKHEAD STEPS	LADDER ONLY
FRONT FENDERS WITH FLAPS	NONE
BOTTOM RAIL	SQUARE NO CLEAN OUT
UPPER CROSS TUBES / ARCH	6
USE ONLY 3 CROSS TUBES BETWEEN FRONT AND REAR CAPS	
FRONT CAP	YES
REAR CAP	NO
TIRE CARRIER	(1) IN MIDDLE ONLY

LIGHTS

LIGHT TYPE	GROTE L.E.D. W/ GROMMET
LIGHT PANEL	3 LARGE-3 SMALL-3 LARGE (SPLIT LIGHT PANEL) OOO ooo OOO
APRON	NONE
STD. MARKER LIGHTS	(5) EACH SIDE 0.0
(5) PER SIDE TOP & BOTTOM PENNY LIGHTS. 1.0	

MID-TURNS	(1) PAIR L.E.D. (COMBO)	
BACK-UP LIGHTS	(1) PAIR L.E.D. BACK UP LIGHTS	0.0
	ADD ONE PAIR OF WORKLIGHTS TO INSIDE FRONT. WIRE TO FRONT IN WATERPROOF SWITCH ON AUX	1.0
AUXILIARY CABLE	7 WAY (ISO)	
	B/U ON BLACK MAIN	
REAR POCKET LIGHTS	(1) PAIR	

GATE

GATE OPERATION	BI-FOLD	0.0
	QUAD LOCKS	1.0
GATE OPTIONS	SOLID .080	
	BLACK DURAPLATE	
HINGE TYPE	BARN DOORS SIDE SWING (ALUM.)	
SAFETY CHAIN	YES	
WINDERS / SAFETY LATCH	NONE	
GATE STEPS	NONE	
TARP HOOKS	NONE	

PRIMARY AXLES

MODEL	CLOSED TANDEM	
NO. OF PRIMARY AXLES	2	
SUSPENSION	MAC FABBED GALVANIZED SINGLE LEAF TAN. (49)	
AXLE SPACING	49	
SUB-FRAME	TANDEM, HI-TENSILE FAB (SPRING RIDE ONLY)	
	USE HENDRICKSON VANTRAAX AIR RIDE SLIDER ASSEMBLY	
AXLES	77.5 IN. 5/8 IN. AXN TP W/ 25K	
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS	
CAM GUARDS	NONE	
HUB AND DRUM	CAST W/ STEEL HUB HP 10 STUD TP, LS, 7 IN.	
TIRES	GENERAL RA 11R 22.5 16 PLY	
WHEELS	STEEL HP 22.5X8.25 - WHITE POWDER COATED	

LIFT AXLES

NO. OF LIFT AXLES	0	
LIFT AXLE SUSPENSION	NONE	
LIFT KIT	NONE	
LIFT AXLE DISTANCE	N/A	
LIFT AXLE	NONE	
LIFT AXLE BRAKES	NONE	
LIFT AXLE CAM GUARDS	NONE	
LIFT AXLE HUB AND DRUM	NONE	
LIFT AXLE TIRES	NONE	
LIFT AXLE WHEELS	NONE	
LIFT AXLE CONTROLS	NONE	
FREE WHEEL VALVE	NONE	

STEERABLE LIFT AXLES

NO. OF STEERABLE AXLES	0	
STEERABLE AXLE SUSPENSION	NONE	
STEERABLE AXLE LIFT KIT	NONE	
STEERABLE AXLE DISTANCE	N/A	
STEERABLE AXLES	NONE	
STEERABLE AXLE BRAKES	NONE	
STEERABLE AXLE HUB AND DRUMS	NONE	
STEERABLE AXLE TIRES	NONE	
STEERABLE AXLE WHEELS	NONE	
STEERABLE AXLE CONTROLS	NONE	

CHASSIS

PIN SETTING	36	
5TH WHEEL PLATE	3/8 LOW PROFILE	
5TH WHEEL PLATE HEIGHT	48 IN. HIGH	

GALVANIZED SUSPENSION HANGERS	INCLUDED W/ SUSPENSION
SUSPENSION CONTROL	ELECTRIC THRU AUX. & BALL VALVE
ABS	(1) 2S1M MERITOR / WABCO
SLACKS	AUTOMATIC
TIRE INFLATION SYSTEM	NONE
AXLE LUBRICATION	5 YR. SYNTHETIC GREASE
HUBODOMETER	NONE
DUST COVERS	NONE
DOLLIES - LANDING GEAR - LANDING LEGS	JOST A451 - (62,500 LB.) - 10 YEAR NO LUBE - STEEL - (REVERSE MOUNT) D.S.
REGISTRATION HOLDER	BETTS PS-1 W/ SIGHT GLASS (ROUND HOLDER)
AIR GAUGE / SYSTEM	YES, IN FRONT
ENCLOSURE FOR SWITCHES	NONE
AIR TANKS	12 IN. ALUMINUM TANK
HYDRAULIC HOSE FITTING	1 IN. X 108 IN. HOSE W/ WING FITTING
FLAPS FRONT OF TIRES	NONE
FLAPS REAR OF TIRES	FLAP BEHIND REAR AXLE
BUMPER	D.O.T. BUMPER

TARP

TARP MANUFACTURER	AERO KWIK LOCK - VINYL
ADDED (2) RIDGE POLES TO TARP.	
TARP CONTROL	MANUAL
TARP COLOR	BLACK
TARP BRACKET	NONE

PAINT

SUSPENSION COLOR	BLACK SOFT COAT
PIN STRIPING	BLACK (931716)