

## Hale Trailer Brake & Wheel A005671-A005676 VIN: 5A1116-5A1121



RENEGADE XN20 (Model: RENLXT40NF*832542)		
Detailed Specifications	General	
SKU	RENLXT40NF*832542	
Capacity	40 Tons in 16-foot Length - GAWR and GVWR Determine Legal Loads	
Length (Trailer Only)	53 feet 1 inches (closed); 77 feet 0 inches (open)	
Width	8 feet 6 inches	
Compatibility	Designed to Accept Optional Third Flip Axle	
Accent Package	Stainless Steel Bumper Insert	
Weight	Est. Configured Weight: 24165# +/- 3%	
	Gooseneck	
Gooseneck Design	Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11 feet 11 inches overall Gooseneck Length) Set Up for Wetline Operation	
Loaded Fifth Wheel Height	50-inch Nominal Loaded Fifth Wheel Height with 5 Ride Height Positions	
Power Source	Set Up for Wet Line Operation	
VIN Plate	Bilingual VIN Plate	
Registration/Document Holder	Install Registration/Document Holder	
	Deck	
Framework	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs	
Deck Design	Flat Level Deck Design	
Deck Length	32 feet 0 inches Clear Deck Length (closed) - 56 feet 0 inches (open)	
_oaded Deck Height	20 inches with 6 inches Ground Clearance	
Crossmembers	On 24 inch Centers	
Deck Lock	First 5 Spaced Approx. 12 inches; Others Every 50 inches	
Flooring	1 3/8 inch Nominal Wood (Full Width)	
Recessed Floor Mounted D-Ring Package	None	
Front Ramps	None - Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats	
Extension Brackets	Outriggers - 16 Pair - 32 Total Removable Swing Type, 1 Pair - 2 Total Removable Hook-On Type	
	Rear Bridge: General	
Front Bogio Bamn	Sloped Steel Bogie Ramp (Full Width)	
Front Bogie Ramp Mini Boom Trough and Traction Cleats	None	
Deck to Bogie Connection	Fixed	
Covered Rear Bogie	Rear Bogie Platform with 1 1/8 inch Wood Floor	
Rear Bogie Height	41 inches	
Connections for Future Axle		
Attachment	Air and Electrical Connections to Go Along with Connecting Ears	
	Rear Bridge: Axles	
Number of Axles	2	
Axle Capacity	25,000 lb. Nominal Capacity Per Axle - NOTE: GAWR Determined By Suspension Type, Brakes, Tires and Other Components	
Axle Spread	54.5 inches (Between Axles)	
Spring Brakes	Spring Brakes (2 Axles)	
Dust Shield	None	
Hubodometer	None	
	Rear Bridge: Suspension	
Suspension	Air Ride with Automatic Controls	
ABS	4S/2M System without Diagnostic Tool and Cable	
Ride Height Control	Automatic/Manual Raise/Lower Control	
Liquid Filled Gauge	Included	
Load Scale	None	
Loud Jeale	None	



**Detailed Specifications** 

Wheels and Tires	
Wheels	8.25 x 22.5 LvL One Buffed Outside/Steel Inside - Hub-Piloted
Tires	255/70R 22.5 H Ply OEM Standard
Inflation	None
	Lighting
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes
Tail Lights	3 Tail Light Package
Marker Lights	8 Marker Lights Per Side Including Mid-Turn
Special	Not Available on This Model
Electrical Receptacle	J560 7-Pin Connector
	Paint
Paint	Fontaine Black Polyurethane Enamel
	Miscellaneous
Lash Rings	12 Pair - 24 Total
Flag Holders	2 Pair Flag Holders
	Additional Options
Flip Axle	None
Dust Shields on Flip Axle	None
	·
	PENEGADE YN20

## **RENEGADE XN20**



RENEGADE XN20 Base Model (Note: Options not shown)



