



Hale Trailer Brake & Wheel

A005693-A005698

VIN: 5A1105-5A1110



RENEGADE X20 (Model: RENLXT40*F*829542)

Detailed Specifications		General	
SKU	RENLXT40*F*829542		
Capacity	40 Tons in 16-foot Length - GAWR and GVWR Determine Legal Loads		
Length (Trailer Only)	48 feet 0 inches		
Width	8 feet 6 inches		
Compatibility	Designed to Accept Optional Flip Box (Gooseneck Extension) and Third Flip Axle		
Accent Package	Stainless Steel Bumper Insert		
Weight	Est. Configured Weight: 20390# +/- 3%		
Gooseneck			
Gooseneck Design	Mechanical Removable with Fixed Guide Rollers - Combination Figure-8 Plate Which Provides 50 inches and 52 inches Loaded - Swing Radius of 81 inches		
Gooseneck Platform	Full-Width Gooseneck Patform with 1 1/8 inch Wood Floor		
Tool Box	None		
Gooseneck Fenders	Aluminum Fenders at Rear of Gooseneck		
VIN Plate	Bilingual VIN Plate		
Registration/Document Holder	Install Registration/Document Holder		
Deck			
Framework	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs		
Deck Design	Flat Level Telescopic Deck Design		
Deck Length	29 feet 0 inches Clear Deck Length (Retracted) - 50 feet 0 inches (Extended)		
Loaded Deck Height	20 inches with 6 inches Ground Clearance		
Crossmembers	On 24-inch Centers		
Flooring	1 3/8 inch Nominal Wood (Full Width)		
Recessed Floor Mounted D-Ring Package	None		
Front Ramps	None - Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats		
Extension Brackets	Outriggers - 14 Pair - 28 Total Removable Swing Type, 1 Pair - 2 Total Removable Hook-On Type		
Rear Bridge: General			
Front Bogie Ramp	Sloped Steel Bogie Ramp (Full Width)		
Mini Boom Trough and Traction Cleats	None		
Deck to Bogie Connection	Fixed		
Covered Rear Bogie	Rear Bogie Platform with 1 1/8 inch Wood Floor		
Rear Bogie Height	41 inches		
Connections for Future Axle Attachment	Air and Electrical Connections to Go Along with Connecting Ears		
Rear Bridge: Axles			
Number of Axles	2		
Axle Capacity	25,000 lb. Nominal Capacity Per Axle - NOTE: GAWR Determined By Suspension Type, Brakes, Tires and Other Components		
Axle Spread	54.5 inches (Between Axles)		
Brakes	16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount		
Spring Brakes	Spring Brakes (2 Axles)		
Dust Shield	None		
Hubodometer	None		
Rear Bridge: Suspension			
Suspension	Air Ride with Automatic Controls		
ABS	2S/2M System without Diagnostic Tool and Cable		
Chain Lift	Chain Lift Included on First Axle When 34-foot Deck is Selected		
Ride Height Control	Automatic/Manual Raise/Lower Control		
Liquid Filled Gauge	Included		
Load Scale	None		

Detailed Specifications

Wheels and Tires	
Wheels	8.25 x 22.5 LVL One Buffed Wheels
Tires	255/70R 22.5 H Ply OEM Standard
Inflation	None
Lighting	
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes
Tail Lights	3 Tail Light Package
Marker Lights	8 Marker Lights Per Side Including Mid-Turn
Electrical Receptacle	J560 7-Pin Connector
Paint	
Paint	Fontaine Black Polyurethane Enamel
Miscellaneous	
Lash Rings	9 Pair - 18 Total
Flag Holders	2 Pair Flag Holders
Additional Options	
Flip Box	None
Flip Axle	None
Dust Shields on Flip Axle	None

RENEGADE X20



[RENEGADE X20 Base Model](#) (Note: Options not shown)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

