



Hale Trailer Brake & Wheel

A005722-A005771

VIN: 213254-213303



ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL PLATFORM LEGEND SD GALVANIZED SEE SECTION
DIMENSIONS LENGTH WIDTH HEIGHT	48'-0" 102", 97" between side rails. Floor, approximately 59 1/2" high at front and 54" at rear.
COUPLING COUPLER PLATE KING PIN LOCATION COUPLER HEIGHT	1/4", 80 000 psi steel, plug welded structure. 30" from front. 48".
STRUCTURE FLANGES WEB GOOSENECK CROSSMEMBERS FLOOR FLOOR FASTENING SIDE RAILS SIDE BOXES RUB RAILS CORNERS X BRACES	44" c/c frame with "CAMBER". 3/8" x 5", high tensile. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer. 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. Aptitong or equivalent, 1 1/8" thick shiplap finished, no preservative. Screws 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets. 3/8" x 2 1/2" shaped steel. Bevelled. Between main beams, full length.
ENDS FRONT RAIL BUMPER HEADBOARD POCKETS BUMPER REAR RAIL	Formed steel, bolted. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. *** Galvanized *** 2 bolted galvanised pockets at front for removable headboard. 2 rubber dock, at the end of rear rail. Formed steel.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM FLASHERS	7 way (SAE J560). Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.



ITEM	DESCRIPTION
LANDING GEAR	Holland, Mark V (LGS-4F315), with mounting plate & solid axles. *** Galvanized ***
SAND SHOES	10" x 10".
CRANK	Road side.
BOGIE	
BASIC MECHANICAL	
BOGIE	Slider, Hutch H-9000, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 6" c/c between locating holes, (48" travel).
MECHANICAL (GROUND AXLES)	
SUSPENSION	Hutch H-9700, tandem, under mount, 49" spread.
U-BOLTS	With nuts at bottom.
SPRINGS	3 leaves, model TRA 2741, 12 000 lbs capacity.
AXLE(S)	Meritor, TN 467_L, 22 500 lbs. capacity.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None (Meritor axles).
BRAKES	16 1/2" standard, FRAS-LE MA212Q+ extended life lining.
BEARINGS	HM 218248 and HM 212049
SLACK ADJUSTERS	Meritor, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omni brake" (30-30). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	General, 11 R 22.5 HT+ 14 ply (41.1")
AIR SYSTEM	
GLAD HANDS	Fixed.
AIR VALVES	Meritor Wabco, ABS, 2 sensors 1 modulator.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber with moose logo and vertical grooves to reduce spray.
SLIDING TRACK	Full length, "LL" extruded aluminum, road side.
WINCHES	Qty: 12, KINEDYNE #1020ZP, zinc plated slider (low profil 5 7/8").
FINISHING	
PAINT	Ready for Galvanized plateform.
BOGIE	One coat of epoxy primer and one acrylic urethane top coats, Color: Grey metallic, code: PPG Q37-939514.
RETROREFLECTIVE TAPES	Axles (wheel end) included. (Tandem). Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
WHEELS OR RIMS	White (power top coat).



ITEM	DESCRIPTION
PAINT	Vin plate to be made of metal. Pre-drill the web prior to galvanizing
ADDITIONAL OPTIONS R	<p>SAME AS U#211419</p> <p>Due to the deep backlogs, material/component availability and price fluctuation, Manac reserves the right to adjust the price based on these instabilities. If needed, Manac will contact the dealer or customer a minimum of 3 months prior to assembly with revised pricing or a change in components. The dealer or customer will have the option to accept the change or cancel the order at that time.</p>
GALVANIZED CHOICES PLATFORM CROSSMEMBERS FRONT RAIL SIDE RAIL REAR RAIL BUMPER	<p>Galvanized choices.</p> <p>Galvanized platform. (no paint)</p> <p>** WARNING: holes parachute shaped required for dripping **</p> <p>Galvanized</p> <p>Galvanized</p> <p>Galvanized</p> <p>Galvanized</p> <p>Galvanized</p>
CONFORMITY	<p>This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.</p>

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.