



## Hale Trailer Brake & Wheel

**A005975-A006004**

**VIN: 34906-34935**



Base Model: FC48x102 Air Slider

Serial #: 34906 - 34935

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 48' - Base Weight 10,380#

OVERALL WIDTH 8' 6"

KING PIN SETTING 30" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

FRONT SKIRT Aluminum Front and Corners

REAR SKIRT Aluminum

BULKHEAD None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6" - Alum- Extruded W/Double L Track

FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg.

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer

FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards

WINCH TRACK Double L Aluminum- Extruded Siderail R/S Only

TIE BAR Curb Side - Full Length - 3/8" x 2"

WINCHES 12 DOUBLE L (+)#75

STRAPS None

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride- Hendrickson - Intraax - 46K -Tandem Slider (AK880)

SUSPENSION LOCATION Slider/Variable

AXLES (2) 22.5K Capacity- Type 30 Chambers- Auto Slacks

AXLE SPACING 49" (+35#)

LIFT AXLE None

DUMP VALVE None

SCALES None

ABS SYSTEM Wabco ABS System 2S/1M

PARKING BRAKES All Axles

DUST SHEILDS None

TIRE INFLATION SYSTEM None

TIRES 11R 22.5- DOUBLE COIN

WHEELS Disc - Hub Piloted - 22.5 Steel

ANTI-SAIL MUD FLAPS Behind Rear Axle

STAKE POCKETS 24" O.C. Sides & 5 Across Rear

RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape

SPOOL Triangular Shaped

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced

TOOLBOX MATERIAL None

TOOLBOX TYPE None

TOOLBOX LOCATION None

CUSTOM LIGHTS None

LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.