



Hale Trailer Brake & Wheel

A006032-A006046

VIN: 34964-34978

Base Model: DC53x102 RAS 22.5

Serial #: 34964 - 34978

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53'

UPPER DECK LENGTH 10'6"

LOWER DECK LENGTH 42'6"

OVERALL WIDTH 8' 6"

KING PIN SETTING 24" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

FRONT SKIRT Aluminum Front and Corners

REAR SKIRT Aluminum

BULKHEAD None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6"-Alum-Extruded W/Double L Track

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer

FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards

WINCHES 12 DOUBLE L (+)#75

WINCH TRACK Double L Aluminum - Extruded Siderail R/S Only

TIE BAR Curb Side - Full Length - 3/8" x 2"

STRAPS None

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride-Hendrickson Intraax - 23K 2 Axle - RAS

SUSPENSION LOCATION R.A.S.- Cal Legal (Center of KP to Center of Rear Axle 40' in Closed Position)

AXLES (2) 22.5K Cap.- Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" - 49"

LIFT AXLE None

DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)

TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind All Axles

STAKE POCKETS 24" O.C. Sides & 5 Across Rear

SPOOL Triangular Shaped

RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced

CONTAINER TWIST LOCKS None

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

DUNNAGE RACK None

TOOLBOX MATERIAL None

TOOLBOX TYPE None

TOOLBOX LOCATION None

LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear

CUSTOM LIGHTS None

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.