



# Hale Trailer Brake & Wheel

A006078-A006082

VIN: 007189-007193



Model: ALUMINUM-ARA

Item	Description
TANK CONSTRUCTION	ARA
CAPACITY	8500 GALLONS
OUTAGE	1 PERCENT (MINIMUM)
CODE	49 CFR 173.247
DESIGN PRESSURE	ATMOSPHERIC
VENTING	ASPHALT TYPE
TEMPERATURE RATING	400 DEGREE
MATERIAL-BARREL	5454-H32 ALUMINUM
SURGE PLATES	(2) ALUMINUM
COMPARTMENTS	ONE
CAPACITY MARKERS	3-DISC
INSULATION	4" FIBERGLASS, 1# DENSITY
ALUMINUM JACKETING	0.040" SIDE SHEETS/0.060" HEADS
REAR DISCHARGE VALVE	6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION.
GATE VALVE	4" AT REAR UNLOADING LINE
FRONT PUMP-OFF VALVE	3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT. FENDER.
THERMOMETER	3" DIAL IN WELL W/ PLEXIGLASS COVER
MANHOLE	20" ASPHALT TYPE WITH SINGLE HOLD DOWN
DEFLECTOR PAN	BENEATH MANHOLE
MANHOLE PLATFORM	4-SIDED, ALUMINUM
MANHOLE OVERFLOW	2" EXTERNAL
HEATING SYSTEM	NONE
LADDER	ALUMINUM-CURBSIDE
WALKWAY	NONE
HOSE TROUGH	20' ALUMINUM MOUNTED ON CURBSIDE.
TIRE CARRIER	NONE
FENDERS	ALUMINUM, FRONT & REAR (WITH MUDFLAPS ON REAR FENDERS)
LIGHTS	L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR
GLAD HANDS	LOW MOUNT
BUMPER-SPLIT TYPE	ALUMINUM, WITH SLOPING OUTLET
CONSPICUITY MARKING	PER DOT REQUIREMENTS
UPPER COUPLER	ADJUSTABLE
LANDING LEGS	MARK V HEAVY DUTY
BOGIE	ALUMINUM
SUSPENSION	INTRAAX AAT25K AIR RIDE TANDEM W/MANUAL EXHAUST VALVE MOUNTED ON REAR CROSS MEMBER
WHEEL END PACKAGE	HXL5 (5 YEAR WARRANTY)



AIR BRAKES	DRUM W/AUTO SLACKS
AIR BRAKES	25,000# RATING (PER AXLE)
BRAKE DRUMS	CENTRIFUSE
ANTI-LOCK BRAKES	2S/2M SYSTEM (2 SENSORS/2 MODULATORS)
AXLES	25,000# BEAM RATING WITH HP BEARINGS. 77 1/2" TRACK
HUBS	DURA-LIGHT
ALUMINUM DISC WHEELS	ACCURIDE 10-HOLE, HUB PILOTED, STANDARD POLISH
TIRES	11R22.5-H
PAINT	CARBON STEEL PARTS ONLY-BLACK
CENTER PAINT BAND	14' WIDE BAND-BLACK, LADDER AND PLATFORM PAINTED BLACK
PLACARD KIT	4 SIDES SLIDE-IN TYPE W/"HOT" CARD
SAMPLE VALVE	3/4", LOW IN REAR HEAD

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.