



Hale Trailer Brake & Wheel
A006276-A006325
VIN: 50929-50978



Detailed Specifications

Velocity Flat 48 Spring Slider (HAVSF12SST)

General	
Model	HAVSF12SST
Length x Width	48 feet x 102 inches
Suspension	Sliding Spring Tandem
Frame Rating	80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads
Kingpin Setting	30 inches
Fifth Wheel Height	49 inches
Axle Spread	49 inches
VIN Plate	Bilingual US/Canadian VIN plate
Estimated Weight	Est. Weight: 11880 lbs. +/-3%
Structural	
Main Beams	130K Load Bearing Flanges
Crossmembers	12 inch Centers - 4 inch Jr. I-Steel
Knee Braces	Fabricated on Approx. 60 inch C/C
Side Rails	6 inch Structural Channel @ 6.5 lbs/ft
Stake Pockets	3/16 inch Steel on 24 inch Centers
Pipe Spools	Double Between Stake Pockets
Rubrail	3/8 inch x 2 1/2 inch Steel
Front Corners	Tapered
Bumper	Weld-On; Meets U.S. Underride Requirements
Winch Track	Steel on Road Side
Bulkhead Pockets	4 - F-5 DOT-Type Steel
Landing Gear	
Landing Gear	Jost A400G19 Steel Landing Gear with Forward and Rear Bracing
Flooring	
Flooring	1 1/8 inch Apitong Wood
Suspension	
Suspension Detail	OEM Standard 3-leaf spring slider - 60 inches adjustable
Number of Axles	2
Axle Spindle	Tapered
Brakes	Spring Brakes, Auto Slacks
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums
Wheel Ends	Oil in Hubs
Tire Inflation System	None Standard
Wheels and Tires	
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD
Tires	11R 22.5 14PR OEM Standard tires
Air System	
Air Line Filters	(2) Meritor In-line Type Installed
ABS	4S/2M - No Cable or Tool
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer



Detailed Specifications

Electrical System

Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side

Paint and Decal

Paint	Black Urethane with Velocity Decals
Conspicuity Tape	Per NHTSA Specs - Installed on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed

Miscellaneous

Mudflaps	1 Set OEM Standard
Sliding Winches	12 standard
Winch Location	All Road Side
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Registration Holder	Install Registration Holder - OEM Standard

Options

Bulkhead	None Standard
Spare Tire Carrier	None Standard
Hubodometer	None Standard
Tool Box	None Standard

Literature

Trailer Literature	Velocity Brochure
--------------------	-----------------------------------

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.