



Hale Trailer Brake & Wheel
A006847-A006850
080066-080069



GENESIS FRAME DUMP

Length	33	BODY SPECIFICATIONS		Body	
Width	96" INBOARD	Tarp	NONE	Accessories	
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP	Tarp Bows	NONE		
Side Mat'l-front	4' - .100 WALL	Tarp Basket	NONE		
-middle	23' - .140 WALL	Tarp Hooks	NONE	TAILGATE	
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16" (10)	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOK	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Slope	NONE
		Body Fenders	18"	Hinges	OVERSLUNG
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Side Swing	YES -W / GRD CNTRL-P/S HINGE
		Inside	NONE	Gataseal	RUBBER
Floor Options	STUB LONGITUDINALS			Safety Latch	ONE EACH SIDE
		Shovel Hgr	INSIDE P/S OF DOGHOUSE	Coal/Grain Door	NONE
Tailgate Control	AIR / FRAME + ELEC CC (4)	Light Panel	FULL - LED: X=LED B/U LIGHTS	Coal Chute	NONE
Body Pkg	NONE		OOOX ooo XOOO (11)	Gate Options	
Options		Marker Lights	LED - 5 PR TOP & BOTTOM		
Vibrator	NONE	MMTS	BELOW RAIL - LED		
Mudflaps	STD + ACROSS REAR (1)	Apron	NONE		

CHASSIS SPECIFICATIONS

Model	TRIAxLE-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	34'				D/S CRANK
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-265 (2)(10)			Elec Coupler	7 WAY + ISO 7 WAY LABELED
Chassis Neck	STD	Distance:			AUXILIARY"
King Pin Setting	18"	From:		Hyd Tank	NONE
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT			Hyd Hose Fitting	WINGNUT
5th Whl Ht	49"	Controls		Hyd Hose Length	108"
Overhang	6"			Tow Hooks	TWO-ONE EACH SIDE
Rear Axle Setting	21.5"	Location		Paint	BLACK SOFTCOAT
K/P To Rear Axle	411.5"	Axe(s)			NONE
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Accessories		Chassis	CHASSIS REAR CM: TAPERED
Susp Control	FRAME + ELEC CC (4)(9)			Options:	W/ DIAMOND PLATE COVER
Susp Spacing	52" - 52" (6)	Brakes			
Susp Options	GALVANIZED HANGERS	Drums			
Springs	AIR	Hubs			
Axles	TP SPINDLES				
Accessories	NONE	Wheels			TIREMAXX PRO INFLATION
Brakes	16-1/2" x 7"				SYSTEM ALL AXLES
Drums	CAST	Tires			
Hubs	10 STUD STEEL				
Wheels	8.25 x 24.5 12 HP				
Tires	11R 24.5 RA H 16 PLY GENER.				

REMARKS:

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION.
2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
3. RIGHT WEIGH OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.
4. WIRED TO AUXILIARY ISO 7 WAY PLUG
5. HEIGHT CONTROL VALVE ON AXLE #2.
6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
7. ALL FRAME SWITCHES TO BE AIR IN BOX ON D/S NEAR LANDING GEAR.
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
9. NO CROSSOVER KITS
10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.
11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG

WEIGHT: 14,036

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.