



Hale Trailer Brake & Wheel

A006868-A006869

VIN: 080182-080183



GENESIS FRAME DUMP

Length	30'	BODY SPECIFICATIONS		Body	
Width	96" INBOARD	Tarp	NONE	Accessories	
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP	Tarp Bows	NONE		
Side Mat'l-front	4' - .100 WALL	Tarp Basket	NONE		
-middle	20' - .140 WALL	Tarp Hooks	NONE		
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16" (10)		TAILGATE
Side Options	NONE	Bulkhead	D/S-MANDOOK	Height	FULL - GENESIS
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Mat'l Thkness	.140 WALL
		Body Fenders	18"	Slope	NONE
Crsnbr Spacing	12"	Ladders (Out)	D/S-REAR	Hinges	OVERSLUNG
		Inside	NONE	Side Swing	YES -W / GRD CNTRL-P/S HINGE
Floor Options	STUB LONGITUDINALS	Shovel Hgr	D/S-FRAME	Gateseal	RUBBER
				Safety Latch	ONE EACH SIDE
Tailgate Control	AIR / FRAME + ELEC CC (4)	Light Panel	FULL - LED; X=LED B/U LIGHTS OOO ooo XOOO (11)	Coal/Grain Door	NONE
Body Pkg	NONE	Marker Lights	LED - 5 PR TOP & BOTTOM	Coal Chute	NONE
Options		MMTS	BELOW RAIL - LED	Gate Options	
Vibrator	NONE	Apron	NONE		
Mudflaps	STD + ACROSS REAR (1)				

CHASSIS SPECIFICATIONS

Model	TRIAXL-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150 D/S CRANK
Length	31'			Chassis Lights	NONE
Width	96"	Independ. Susp(s)		Elec Coupler	7 WAY + ISO 7 WAY LABELED AUXILIARY"
Hoist	85-250 (2)(10)	Distance:		Hyd Tank	NONE
Chassis Neck	STD	From:		Hyd Hose Fitting	WINGNUT
King Pin Setting	18"	Controls		Hyd Hose Length	108"
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	Location		Tow Hooks	TWO-ONE EACH SIDE
5th Whl Ht	49"	Axle(s)		Paint	BLACK SOFTCOAT
Overhang	6"	Accessories		Chassis	CHASSIS REAR CM: TAPERED Options: W/ DIAMOND PLATE COVER
Rear Axle Setting	21.5"	Brakes			
K/P To Rear Axle	332.5"	Drums			
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Hubs			
Susp Control	FRAME + ELEC CC (4)(9)	Wheels			
Susp Spacing	52" - 52" (6)	Tires			
Susp Options	GALVANIZED HANGERS				
Springs	AIR				
Axles	TP SPINDLES				
Accessories	NONE				
Brakes	16-1/2" x 7"				
Drums	CAST				
Hubs	10 STUD STEEL				
Wheels	8.25 x 24.5 12 HP				
Tires	11R 24.5 RA H 16 PLY GENER.				

REMARKS:

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION.
2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
3. AIR IN THE BOX - OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.
4. WIRED TO AUXILIARY ISO 7 WAY PLUG - SUSPENSION EXHAUST WIRED TO AUX ISO 7 WAY PLUG
5. HEIGHT CONTROL VALVE ON AXLE #2.
6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC **POWER TO RAISE** (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
7. ALL FRAME SWITCHES TO BE IN **BOX** ON D/S NEAR LANDING GEAR.
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
9. NO CROSSOVER KITS WEIGHT: 13,485
10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.
11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.