



Hale Trailer Brake & Wheel

A006891-A006892
VIN: 001224-001225



53ET3XP		
53 ft. Tridem		
Paving & Recovery		
		Base Weight: 18,540
TRAILER	Overall Length	53 ft.
	Overall Width	102 in. (Over width permits may be required)
	Weight lbs +/- 2%	19759, including options
	Spacing	*NPO*: King pin to center of rear axle not to exceed 42 ft 11 in.
GOOSENECK	Coupler	Weld in King Pin
	Coupler Plate	5/16 in. Hi-Tensile, 48 in. Height
	Coupler Location	18 in.
	Length	10 ft. 6 in.
	Cross Members	Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C
	Swing Clearance	83 in.
	Floor	1 1/8 in. Shiplapped Apitong/Keruing
	Web	1/4 in. Hi-Tensile
DECK	Deck Length	35 ft. 1 in.
	Loaded Deck Height	35 in.
	Main Frame	3/8 in. x 5 in. Top Flange and 1/2 in. x 5 in. Bottom 100 KSI
	Cross Members	Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces
	Side Rail	6 in. @ 8.2 Channel
	Web	3/16 in. Hi-Tensile
	Landing Gear	Dual 2 Speed
	Floor	1 3/8 in. Shiplapped Apitong/Keruing with 3/16 in. Deckplate over the wheels
	In Floor Chain Box	1 - located at rear of Gooseneck, 1 - located at rear of main deck, with deckplate covers included
SUSPENSION/AXLES	Axles	25,000 lbs Capacity
	Air Lift	Air Lift c/w Control Box: Lead Axle
	Spread	*NPO*: 60 in.
	Suspension	Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure
	Brakes	Quick Change 12 1/4 in. x 7 in.
	Brake Chamber	#3030, All Axles
	Air Brake System	2S/1M
	Slack Adjusters	Automatic
	Camshafts	28 Spline Non Enclosed
	Hubs & Drums	8 Stud Unimount C / W Cast Drums
	Tires	Tire Upgrade to 245/70R17.5 Continental HTL2 ECO
	Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)
BEAVERTAIL	Length	6 ft. @ 8 degree slope, Planked
RAMPS	Rear	45 in X 11 ft. Air Operated Bi Fold - Planked

53ET3XP		
53 ft. Tridem		
Paving & Recovery		
		Base Weight: 18,540
<div>RAMPS</div> <div> Main Deck to G/N12 ft. Inset Full width Air Operated - Planked Main Deck to G/N*NPO*: Ramp Prop Access Covers </div>		
<div>GENERAL SPECIFICATIONS</div> <div> Electrical SystemModular, Vapor Proof GROTE Ultra Blue LightsLED CMVSS 108 / FMVSS 108 Front ConnectorSAE J560 7 Pin Rear Connector4 Pin Plug FinishingPreparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked ColorBlack Mudflaps1 set of BWS at rear Load Securement* Moulded Rub Rail, Stake Pockets and Spools 24 in. OC (Over all Width affected by option as shown) Load Securement15, Pair of in Floor Flush Mounted D-Rings: 3 pr. GNK, 2 pr. BT, start directly after front ramp - 10 pr. Main Deck, evenly spaced </div>		