



HALE

TRAILER

BRAKE & WHEEL

Hale Trailer Brake & Wheel

A006903-A006908

VIN: S006622-S006627

TK80SA 2 axle Sliding Axle trailer; 80,000 lbs uniform / 50,000 17333-80SA

17333 - STANDARD EQUIPMENT

Perimeter Frame Gooseneck Design	Air and electrical lines contained in protective track
Hydraulic sliding axles	Single recessed winch roller at front of deck
Tilting main deck - forms a ramp to upper deck	4 beam main frame construction
No traveling hydraulic lines for sliding axle operation	Rubber mounted sealed lights with sealed harness system
Side by side 2-stage cylinder, closed in travel position	Red & white conspicuity markings

Item #	Category	Description	Weight (lbs)	Qty
17333	Open Deck	TK80SA 2 axle Sliding Axle trailer; 80,000 lbs uniform / 50,000 lbs in 10 ft.		
17336	Overall Length	49'-11" overall length		
17339	Overall Width	102" wide		
17342	Fifth Wheel / King Pin	49" loaded fifth wheel height		
17345	Upper Deck	9'0" Straight drop upper deck (14" kingpin setting with 86" swing clearance)		
17346	Upper Deck	No Headboard		
17350	Upper Deck	2 side access tool boxes at front of upper deck		
17352	Winch	20,000 lb. hydraulic winch with level wind (mounted above king pin) Includes 9/16 x 80' cable		
17358	Winch	Delete Winch guard	(61)	
17359	Winch	Winch Cable Skid Plate on Upper Deck		
17362	Hydraulics / Controls	PTO hydraulic tilt		
17366	Hydraulics / Controls	Push - Pull style hydraulic valve controls w/ full-function wireless remote controls (Dual side controls)		
17367	Landing Gear	2 Speed park stands (crank road side)		
17370	Main Deck	Triangle cutouts		
17371	Main Deck	3" crossmembers on 12" Cross member spacing centers		
17374	Main Deck	Approximately 7 degree load angle / 15 degree dump angle (17.5 tires & 48' OAL trailer)		
17375	Decking, Main Deck	1 3/8" (NET) apitong deck raised		

17380	Decking, Approach Plate	3/8" smooth approach plate with 4-way slots on approach plate		
17383	Tie Downs	Internal 2-way key slots on approximately 24" centers length of trailer in inner and outer beams		
17390	Suspensions / Axles	Air Ride suspension		
17391	Suspensions / Axles	Air Ride raise & lowering control panel on upper deck with liquid filled guage		
17392	Suspensions / Axles	25,000 lb. capacity axles		2
17401	Axle Spacing	50" Axle Spacing		
17404	Brakes	12.25 X 7.5 Drum brakes (For 37.5" deck height, select 17.5 wheels and tires)		
17405	Brakes	4S2M ABS Brakes		
17406	Hub / Drum	Steel hub-piloted - Cast drum - tapered spindle (per complete axle)		2
17410	Tire & Wheel Size	For 37.5" deck height, select 17.5 wheels and tires		
08182	Wheels (inside)	6.75 x 17.5 8-hole steel disc wheel		4
15004	Wheels (outside)	6.75 x 17.5 8-hole polished (XP) aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel	(96)	4
10058	Spare Wheel	No Spare Wheel		
18103	Tires	Continental 235/75R17.5 HTL2 - 18 ply (tire only) (per tire) ILO Std Continental 245/70R17.5 HTL2 - 18 ply	(544)	8
10059	Spare Tires	No spare tire		
17412	Flaps, Mud Guards & Fenders	Mudflaps		
17413	Lights / Electrical	Grote Electrical system (meets DOT regulations)		
17414	Lights / Electrical	Single Mid-turn signal w/ clearance lights X-O-X (whole trailer)		
17416	Lights / Electrical	3rd tail light package		
17422	Flagholders	Flag Holders at rear of trailer		
17424	Miscellaneous	Central located lube system		
09998	Paint	Alternative Option Selected. See Add'l Options Section Below.		
08024	Paint	S7203 Black with white decals		

17333-Additional Options

Item #	Category	Description	Weight (lbs)	Qty
17433	Miscellaneous	Fold-down step and handle driver side		
17434	Miscellaneous	Fold-down step and handle curb side		
17395	Suspensions / Axles	PSI Tire Inflation System (2 axle)		
75692	Custom Options	75692 TK80-110SA - Hot dip galvanized in lieu of paint. Note: some bolt-on items such as landing gear, axles, suspension will be painted		
78668	Paint / Decals - Special	78668 TK110SA - Paint standard color over galvanized trailer only on outside face of outside beams (road side and street side) of upper & lower decks, and very front of trailer. Some overspray on inner frame work is acceptable.		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.