



Hale Trailer Brake & Wheel  
A006934-A006947  
VIN: 548171- 548178 & 550379-550384



## Detailed Specifications

### Infinity Flat 48 Air Slider (HAICF12SAT)

General	
Model	HAICF12SAT
Length x Width	48 feet x 102 inches
Suspension	Sliding Air Tandem
<b>Frame Rating</b>	<b>80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads</b>
Kingpin Setting	30 inches
Fifth Wheel Height	49 inches
Axle Spread	49 inches
VIN Plate	Bilingual US/Canadian VIN plate
Estimated Weight	Est. Weight: 10580 lbs. +/-3%
Structural	
<b>Main Beams</b>	<b>130K Load Bearing Flanges</b>
Crossmembers	12 inch Centers - 4 inch Jr. I-Steel
<b>Single Coil Hauling Package</b>	<b>Included</b>
Knee Braces	Fabricated on Approx. 60 inch C/C
<b>Side Rails</b>	<b>Exclusive Revolutionary RASR Rail Technology - One Piece Routed Aluminum Designed for Strength and Impact</b>
<b>Stake Pockets</b>	<b>Routed Aluminum on 24-inch Centers (2 Load Securement Openings in Between Stake Pockets)</b>
<b>Rubrail</b>	<b>Integrated with Side Rail</b>
Front Corners	Tapered Steel
Bumper	Weld-On; Meets U.S. Underride Requirements - Painted Steel
<b>Winch Track</b>	<b>Full-Length Integrated Double L Type Aluminum on Both Sides</b>
Chain Cargo Tie Downs	15 Pair - Recessed in Siderails
Bulkhead Pockets	4 - DOT Type Bulkhead Pockets Only - Welded to Front
Landing Gear	
Landing Gear	Jost A400G19 Steel Landing Gear with Forward and Rear Bracing
Flooring	
Flooring	1 1/8 inch Aluminum with 4 Apitong Wood Nailer Strips
Suspension	
Suspension Detail	Hendrickson AAZNT46K Intraax Air Ride Slider - 60 inches Adjustable
Number of Axles	2
Axle Spindle	Tapered
Brakes	Spring Brakes, Auto Slacks
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums
Wheel Ends	Grease in Hubs - *** 5-Year Wheel End Warranty ***
Tire Inflation System	None Standard
Air Lift	None Standard
Wheels and Tires	
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD
Tires	295/75R 22.5 14PR OEM Standard tires



## Detailed Specifications

Air System	
Air Line Filters	(2) Meritor In-line Type Installed
ABS	4S/2M - No Cable or Tool
Full System Dump	Auto Glad Hand Dump Installed
Control Box	Standard Mount of Controls on Slider Frame
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer
Electrical System	
Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side
Paint and Decal	
Paint	Black Urethane on Steel Parts with Infinity Decals
Conspicuity Tape	Per NHTSA Specs - Installed in Recess on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed
Miscellaneous	
Mudflaps	1 Set OEM Standard
Sliding Winches	12 standard: Sliding Rope Hook/Winch Strap Hook Retainers
Winch Location	Equal Both Sides
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Sliding J-Hook for Strap with Ring	None Standard
Registration Holder	Install Registration Holder - OEM Standard
Options	
Bulkhead	None Standard
Spare Tire Carrier	None Standard
Hubodometer	None Standard
Tool Box	None Standard
Literature	
Trailer Literature	<a href="#">Infinity Brochure</a>

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.