

## Hale Trailer Brake & Wheel A007198-A007212 VIN: 64737-64751



\_\_\_\_\_\_

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 15.1 Units

STANDARD SPECIFICATIONS: CTSSF-45

Type: Peerless dual axle, transport semi-trailer

Design: Box design, flat floor, end dump, live floor

Construction: .063 skin stressed aluminum with aluminum exterior posts on 21.5" centers, bevelled corners

Unloading Time: Approximately 8 minutes

Capacity: 15.1 units (112.2 cu yd)

Dimensions: 45' long, 8' 6" wide, 13' 6" high, 37" king pin location, 36" rear axle from rear of trailer

Tires: Eight (8) **11:00** x **22.5** radial tires

Wheels: Eight (8) 22.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount

Axles: 25,000# cap., 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick

change brake shoes, auto slacks

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: Four spring three leaf tandem, (Hutch H9700T)

Landing Gear: Two speed, crank on driver's side (Holland Atlas 55)

King Pin: Standard SAE, heat treated, 37" setting, 51" height, 5/16" plate – 2 beam

Cross Sills

& Decking Keith 7/32" with wear strips, 3" cylinder, rubber seals, standard live floor, 4" Jr. I-Beams on 22" centers with

aluminum sub-deck,

Top: Flat design, open top, single center tie

Top Cover: Shur-lok roll over tarp – with telescoping pole "wil-slip" cap, rear crank - handle holders on both sides –

black vinyl - Flat caps



Tarp Bows: tarp bows located every 4', on 3" arched tarp bows

Safety Screens: Expanded metal over drive and under front

Rear Door: Full opening, side hinged, skinned with solid aluminum, Offset Door Hinges

Ladders: One located at front with safety loop and one located at rear (front ladder mounted to headboard)

Rope Hooks: Furnished

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt

Glad Hands: Standard mounted on road side of headboard

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights

all lights to be LED

Reflectors: Legal DOT

Paint: Aluminum natural, steel components primed and painted Black

Weight: Approximately 14,245#