



Hale Trailer Brake & Wheel

007222-007226

TRANSPORT	
MODEL	Aluminum-ARA
TANK CONSTRUCTION	ARA
CAPACITY	7250 GALLONS (7500 GALLONS SHELL FULL)
OUTAGE	1 PERCENT (MINIMUM)
CODE	49 CFR 173.247
DESIGN PRESSURE	ATMOSPHERIC
VENTING	ASPHALT TYPE
TEMPERATURE RATING	375 DEGREE
MATERIAL-BARREL	5454-H32 ALUMINUM
SURGE PLATES	(2) ALUMINUM
COMPARTMENTS	ONE
CAPACITY MARKERS	3-DISC
INSULATION	4" FIBERGLASS, 1# DENSITY
ALUMINUM JACKETING	0.040" SIDE SHEETS/0.060" HEADS
REAR DISCHARGE VALVE	6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION.
FRONT PUMP-OFF VALVE	3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT. FENDER.
THERMOMETER	3" DIAL IN WELL W/ PLEXIGLASS COVER
MANHOLE	20" ASPHALT TYPE
DEFLECTOR PAN	BENEATH MANHOLE
MANHOLE PLATFORM	4-SIDED, ALUMINUM
MANHOLE OVERFLOW	2" EXTERNAL
HEATING SYSTEM	NONE
LADDER	ALUMINUM-CURBSIDE
WALKWAY	NONE

HOSE TROUGH	NONE
TIRE CARRIER	NONE
FENDERS	ALUMINUM, FRONT & REAR (WITH MUDFLAPS ON REAR FENDERS)
LIGHTS	L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR
GLAD HANDS	LOW MOUNT
ALUMINUM BUMPER-SPLIT TYPE	WITH SLOPING OUTLET
CONSPICUITY MARKING	PER DOT REQUIREMENTS
UPPER COUPLER	ADJUSTABLE
LANDING LEGS	2-SPEED, CURBSIDE CRANK WITH ALUMINUM MOUNTING FRAME. INCLUDES HORIZONTAL CROSS BRACE
BOGIE	ALUMINUM
SUSPENSION	INTRAAX AANT230 AIR RIDE TANDEM W/AUTO DUMP VALVE
OIL SEALS	STEMCO
AIR BRAKES	16.5" X 7" W/AUTO SLACKS
BRAKE DRUMS	CENTRIFUSE
ANTI-LOCK BRAKES	4S/2M SYSTEM (4 SENSORS/2 MODULATORS)
ROLL STABILITY	MERITOR
AXLES	23,000# BEAM RATING WITH HP BEARINGS.
HUBS	ALUMINUM
WHEELS	MACHINE FINISHED ALUMINUM, 10-HOLE, HUB PILOTED
TIRES	11R22.5-G
PAINT	STEEL PARTS ONLY-BLACK
CENTER PAINT BAND	12' WIDE BAND-BLACK
PLACARD KIT	SLIDE-IN TYPE, 4 SIDES WITH HOT PLACARDS
SAMPLE VALVE	3/4"
HUBODOMETER	DRIVER SIDE FRONT AXLE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.