Hale Trailer Brake & Wheel
A007560-A007568
VIN: 36250-36258

DORSEY
ESTABLISHED 1911

Base Model: DF53x102 BTR Air Spreads
Serial #:36250 - 36258
components description
CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 53' - Base Weight 13,990# - Including Length of Beavertail
UPPER DECK LENGTH 10'6"
LOWER DECK LENGTH 38'1"
DOVETAIL 53.13" - Steel Smooth Plate & Traction Bars
OVERALL WIDTH 8' 6"
KING PIN SETTING 24" - Tapered Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
MAINFRAME 26" Fab.-PreCannb.l-Beams-(80K Pkg)
BULKHEAD None
SIDE RAILS 6" - 6.5# Per Foot
TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE NONE
FLOOR DECKING 1-1/8" Apitong
WINCHES 12
WINCH TRACK Steel Slide Entire Length of Drivers Side
STRAPS None
LANDING GEAR Two Speed - Jost A500
SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles - 22.5
SUSPENSION LOCATION King Pin to Center of Rear Axle 43'
AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)
AXLE SPACING 10'2" Wide Spread
DUMP VALVE Manual-Position In Rear Skirt Gusset D/S-Dump All Axles
LIFT AXLE None
SCALES None
PARKING BRAKES All Axles
ABS SYSTEM Wabco ABS System 2S/1M
DUST SHEILDS None
WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)
TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM None
STAKE POCKETS 24" O.C. & 4 Across Front
ANTI-SAIL MUD FLAPS Behind 2 Axles
PIPE SPOOLS Double
RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape
DOCK BUMPERS None
LOADING RAMPS (2)-Spring Assisted
CONTAINER TWIST LOCKS None
CARGO TIE DOWN None
TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS None
PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted