

Hale Trailer Brake & Wheel A007658-A007672 VIN: A1653-A1667



Detailed Specifications

DSSXT859492) General
XCA5390SSXT859492
100,000 lbs distributed - self-supporting, properly blocked
53 feet 0 inches
8 feet 6 inches
Est. Configured Weight: 17420# +/- 3%
Gooseneck
24 inches Deck
49 inches
OEM Standard
None Start Contract Charles
4 - F-5 DOT-Type Steel
Minimum Grade 80 Flanges
12 inch Centers - 4 in Jr I-Steel
Approx. Every 5 feet
Tapered
6 inch Structural Channel @ 6.5lbs/ft
3/16 inch Steel on 24 inch Centers
Single Pipe Spool
2 1/2 inch x 3/8 inch Thick HD Mill Formed Steel
1 1/8 inch Wood
Full-Length Steel on Roadside
12 - without Straps
None
Inside Track System
None
Meets Underride Requirements
1 Set - Fontaine
Bilingual VIN Plate
Install Registration/Document Holder
Rear Bridge: Axles
2
49 inches
Spring Brakes, Auto Slacks
None
10-Hole Hub-Piloted with Outboard Cast Drums
Rear Bridge: Suspension
Sliding Spring Tandem Hutch H-9700 3 Leaf Spring Slider - 60 inch Adjustable
2S/1M - No Cable or Tool
None
None
None



Detailed Specifications

	Wheels and Tires
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-painted White
Tires	11R 22.5 OEM Economical
Hubodometer	None
Inflation	None
Wheel Ends	Grease in Hubs
	Lighting
Electrical System	Sealed Harness and LED Lights with 4 inch Flush Mounted Amber Strobes (No Battery Backup)
Tail Lights	3 Lights/Side, 3 Lights/Side on Rear
	Paint
Paint	Fontaine Black Polyurethane Enamel
	Terms
Please Note	Price Includes Commodity Surcharges
Commercial Terms	Ex Works- Springville, AL, USA
	XTP5390SS2



XTP5390SS2 Base Model (Note: Options not shown)



