

Hale Trailer Brake & Wheel A007739-A007744 VIN. 2123U0-212317





	VIN: 219308-219314	
ITEM	DESCRIPTION	
TYPE	PIN ON AXLE FOR PLATFORM	
DIMENSIONS		
LENGTH	61 1/2".	
WIDTH	102".	
COUPLING		
COUPLER PLATE	For anchor joints, 4 x 2" dia. rods and bushings.	
STRUCTURE		
FLANGES	1/2" x 6", 100 000 psi steel.	
WEB	3/16" plate, 80 000 psi steel. 13 1/2" high.	
ENDS		
BUMPER	Rectangular steel tubing.	
	Including supports with flag and excessif width sign.	
ELECTRICAL		
FRONT CONNECTOR	Cord with 7 ways connector.	
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.	
MAIN SYSTEM	Grote Ultra blue LED, sealed beams, in a closed back rubber grommet.	
	(tail lights with male pins #54332, markers #47122 (2 1/2" dia.),	
	licence light #60280-M).	
STROBE LIGHTS	(2), installed (1) on each side, (Grote 77353 amber) (rubber grommet)	
SWITCH	Sealed, to activate strobe lights, installed **in the control box**.	
BASIC SUSPENSION		
BOGIE	Fixed.	
SUSPENSION	Hendrickson HT-250US (9), single.	
U-BOLTS	With nuts at top.	

SPRINGS

RIMS

Hendrickson, HP-S506, 27 000 lbs. capacity. AXLE(S)

SPIDERS Welded. **CAM SHAFTS** 28 splines. 77 1/2". **TRACK**

DUST SHIELDS None (Hendrickson axles).

BRAKES 16 1/2" standard, long life H26-HXS Hendrickson lining.

BEARINGS HM 518445.

SLACK ADJUSTERS Meritor, automatic, 28 splines (6").

Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. **SEALS**

BRAKE CHAMBERS T.S.E. brake, "Omnibrake" (30-30), long stroke.

(4 years warranty by T.S.E. for parts only).

HUBS AND DRUMS WEBB, 10 studs disc hubs, balanced drums 117 lbs,

outboard mount, 285.75mm B.C., single flange nuts.

For dual aluminium wheels. (Heavy duty 25000 lbs cap.) 22.5 x 8.25, disc (10 holes),

285.75mm B.C., single flange nuts, 2 hand holes.

TIRES Continental, 275/70 R 22.5 HSR2 SA

18 ply (38.0")





ITEM	DESCRIPTION
AIR SYSTEM	
GLAD HANDS	Fix.
AIR VALVES	Sealco, synflex 3/8" diameter.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING	
PAINT	No paint nor primer applied on. Structure prepared and shipped ready to be
	galvanized.
	(base 78106100)
AXLE(S) PAINTED	*** PAINTED GRAY ***
HUBS	*** PAINTED GRAY ***
WHEELS OR RIMS	White.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108.
	Gray and red, each side, fully covers rear bumper.
ADDITIONAL OPTIONS	SAME AS U#205763
UNIT COUPLED TO	Job:
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG
	regulations come into force prior to the production of the trailer(s),
	Manac will have the obligation to ensure the trailer(s) produced meet
	minimum GHG guidelines. Any modifications required to meet the GHG
	regulations will be added to the initial purchase price and charged back to
	the customer.