



Hale Trailer Brake & Wheel
A007745-A007753
VIN: 215294-215302



ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, TELESCOPIC STEEL DROP PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	71'-0 opened.
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61" high at front and 34" at the bumper.
DROP HEIGHT	25", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high and 16 1/2" above suspension.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12 1/4" high, 48" straight behind king pin.
CROSSMEMBERS	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanised, 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" high. Galvanized front and rear bolted sills.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Over tires at rear, checker plate 1/8".
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
STRUCTURE	1/4" steel rod welded at a flange to attach electrical harness.
ENDS	
FRONT RAIL	9 gauge formed steel.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanised pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear with a small bumper in each corner and 3/8" x 2 1/2" shaped steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.



ITEM	DESCRIPTION
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, tail lights with male pins #53252, (10 diodes) markers #47122 (2 1/2" dia.) and #47962,73 (MicroNova), licence light #60291.
TURN SIGNAL	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
REAR ADD. CONNECTOR	4 way.
STROBE LIGHTS	(2), installed (1) on each side, (Grote 77353 amber) (rubber grommet)
SWITCH	Sealed, to activate strobe lights, installed **in the control box**.
LANDING GEAR	Holland, Mark V (LGS-4F115), with mounting plate, galvanized.
SAND SHOES	10" x 11 1/2".
CRANK	Road side.
BOGIE	
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (6.5), tandem, 60" spread. *** CAL LEGAL W/REAR AXLE LIFTED ***
LIFT DEVICE	Hendrickson HT-250US (6.5) with Manac center lift. Located at 60" rear of tandem. *** Controlled manually *** *** Only 1 1/2" of clearance from the ground if used at rear. *** *** NO WARRANTY ON THE TIRES NOR GROUND AXLES, (FLAT SPOT) ***
U-BOLTS	With nuts at bottom.
SPRINGS	Air.
AXLE(S)	AXN, TA250T, 20 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None.
BRAKES	12 1/4" standard, AXN R23 lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	Haldex S-ABA, automatic, curved, 28 splines, (6").
SEALS	Stemco, "Platinum Performance System". Including "Guardian" seals, Pro-Torq spindle nuts, Integrated sentinel hub caps with Synthetic oil, Mobil Delvac 75W-90. (3 year warranty by Stemco for parts only).
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	WEBB, 8 studs disc hubs, drums 93 lbs, outboard mount, 275mm B.C., single flange nuts. For dual steel wheels or single wheels.
RIMS	17.5 x 6.75, disc (8 holes), 275mm B.C., single flange nuts, 4 hand holes.
TIRES	Continental, 235/75 R 17.5 HTL-2 ECO-PLUS 18 ply (31.6")
AIR SYSTEM	
GLAD HANDS	Fixed.
AIR VALVES	Meritor Wabco, ABS, 2 sensors 1 modulator.
VALVE(S)	Fast-brake kit.
VALVE	Quick and brake release valves on air lift.



ITEM	DESCRIPTION
VALVE	Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table.
CONTROL BOX	Stainless steel.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
WINCHES	Qty: 12, KINEDYNE #1020ZP, zinc plated slider (5 7/8").
SLIDING TRACK	Full length, "LL" extruded aluminum, road side.
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
EXTRA MUD FLAPS	Qty: 2, rubber. Located: 1 at front of landing gear in between main frames, to protect roller and 1 at front of suspension in between main frames, to protect air boosters.
FINISHING	
PAINT	No paint & no primer on the trailer.
FINISHING	Trailer prepared & shipped to be galvanized.
AXLE(S) PAINTED	*** Painted Manac Gray code: Q37M939514 ***
HUBS	*** Painted Manac Gray code: Q37M939514 ***
WHEELS OR RIMS	Powder top coat white.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.
R	Vin plate to be made of meal. Pre-drill the web prior to galvanizing.
ADDITIONAL OPTIONS	
R	SAME AS U#211702 Due to the deep backlogs, material/component availability and price fluctuation, Manac reserves the right to adjust the price based on these instabilities. If needed, Manac will contact the dealer or customer a minimum of 3 months prior to assembly with revised pricing or a change in components.
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.