



**FRAME DUMP TRAILER**

**Hale Trailer Brake & Wheel**  
**A007883-A007885**  
**VIN: 080848-080850**



**BODY SPECIFICATIONS**

<b>Length</b>	26' - STEEL TUB	<b>Tarp Bar</b>	NONE	<b>Body</b>	
<b>Width</b>	96"	<b>Tarp</b>	NONE - SEE NOTE (2)	<b>Accessories</b>	1 - 2" DIA. LIGHT IN EACH REAR POST
<b>Side Height</b>	62" (60 + ANGLE)	<b>Bow Holders</b>	NONE		
<b>Top Rail</b>	1/4" x 4" x 6" (1)	<b>Tarp Bows</b>	NONE		
<b>Side Material</b>	1/4" AR 450	<b>Tarp Basket</b>	NONE		
	ANGLE ON TOP RAILS	<b>Doghouse</b>	STD		<b>TAILGATE</b>
	BH & GATE FLUSH W/ ANGLES	<b>Bulkhead Mat'l</b>	1/4" AR 450 - SLOPE NOSE	<b>Height</b>	FULL + ANGLE
<b>Side Options</b>	ANGLE-1/4" x 2-1/2" x 2-1/2"	<b>Bulkhead</b>	DIAMOND PLATE HOIST COVER	<b>Mat'l Thkness</b>	1/4" AR 450
<b>Floor Mat'l</b>	1/4" AR 450	<b>Options</b>	BH & TG FLUSH W/ CAP ANGLE	<b>Slope</b>	NONE
	24'-8" INSIDE FLOOR LGTH	<b>Body Fenders</b>	FRONT w / 10" RUBBER FLAP	<b>Hinges</b>	OVERSLUNG
<b>Crsmbr Spacing</b>	12" SPACING	<b>Ladders (Out)</b>	RUNG STYLE-BULKHEAD D/S D/S REAR		AIR POWER LIFT - INTERNAL
		<b>Inside</b>	NONE	<b>Gateseal</b>	NONE
<b>Floor Options</b>	4" x 6" LONGITUDINALS	<b>Shovel Hgr</b>	NONE	<b>Safety Latch</b>	ONE EACH SIDE
	CENTER BOLSTER @	<b>Dirt Shedders</b>	ALUM SIDE SKIRTS - FULL		14" UP FROM BOTTOM
	MIDDLE OF TOP RAIL	<b>Light Panel</b>	NONE	<b>Coal/Grain Door</b>	NONE
<b>Tailgate Control</b>	FRM SWITCH + Elec CC	<b>Marker Lights</b>	LED - 2 PR BOTTOM	<b>Coal Chute</b>	NONE
<b>Body Pkg Options</b>	ALUM SIDE SKIRTS - FULL LENGTH	<b>MMTS</b>	INSTALL IN BOLSTER	<b>Gate Options</b>	2" x 2" ANGLE ON TOP OF GATE
<b>Vibrator</b>	NONE	<b>Apron</b>	NONE		SOLID WELD ON ANGLE
<b>Mudflaps</b>	STD +				FRAME SWITCH FOR LIFT
	ACROSS REAR CHASSIS				

**CHASSIS SPECIFICATIONS**

<b>Model</b>	TANDEM	<b>ABS</b>	4S / 2M	<b>Tire Carrier</b>	NONE
<b>Beam Mat'l</b>	16" STEEL @ 31#/FT			<b>Landing Gear</b>	2 SPEED JOST A450
<b>Length</b>	25' 6"				D/S CRANK
<b>Width</b>	96"	<b>Independ. Susp(s)</b>		<b>Chassis Lights</b>	OO ooo OO
<b>Hoist</b>	85-220		NONE	<b>Elec Coupler</b>	7 WAY + ISO 7 WAY
<b>Chassis Neck</b>	TANDEM	<b>Distance:</b>		<b>Hyd Tank</b>	NONE
<b>King Pin Setting</b>	18"	<b>From:</b>		<b>Hyd Hose Fitting</b>	WINGNUT
<b>5th Whl Plate</b>	3/8" + 3" x 7" Hoist Tubes	<b>Controls</b>		<b>Hyd Hose Length</b>	108"
<b>5th Whl Ht</b>	51"			<b>Tow Hooks</b>	NONE
<b>Overhang</b>	6"	<b>Location</b>		<b>Paint</b>	FRAME - BLACK
<b>Rear Axle Setting</b>	21-1/2"	<b>Axle(s)</b>			BODY - BLACK
<b>K/P To Rear Axle</b>	266.5"	<b>Accessories</b>		<b>Tarp Bar Tape</b>	N/A
<b>Suspension</b>	AAT30K / E2-1			<b>Chassis Options:</b>	
<b>Susp Control</b>	FRAME SWITCH + AIR CC	<b>Brakes</b>			
<b>Susp Spacing</b>	52"	<b>Drums</b>			SQUARE OFF REAR CHASSIS
<b>Susp Options</b>	25,000 # GAWR	<b>Hubs</b>			
<b>Springs</b>	AIR	<b>Wheels</b>			MUDFLAP ON CHASSIS
<b>Axles</b>	TP SPINDLES - 25K GAWR	<b>Tires</b>			
<b>Accessories</b>	METAL HUBCAPS				
<b>Brakes</b>	16-1/2" x 7"				
<b>Drums</b>	CAST				
<b>Hubs</b>	10 STUD STEEL				
<b>Wheels</b>	8.25 X 24.5 4 STL/4 HP (3)				
<b>Tires</b>	11R 24.5 RA H 16 PLY (4)				

**REMARKS:** REF 78153

1. BOLSTER TO BE IN MIDDLE OF TOP RAIL
2. DRILL ACCESS HOLE & GROMMET AT TOP D/S OF BULKHEAD FOR FUTURE TARP WIRE THROUGH TOP RAIL TO REAR OF BODY
3. STEEL INSIDE / HIGH POLISHED ALUMINUM OUTSIDE
4. 11R 24.5 RA 16 PLY GENERALS
5. OIL FILLED AIR GAUGE PLUMBED TO SUSPENSION AND MOUNTED IN CHASSIS CROSSMEMBER-AIR IN THE BOX

**WEIGHT:** 15,421

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.