



# Hale Trailer Brake & Wheel

A008344-A008368

VIN: 553057-553081



## Velocity Drop Deck 48 Wide Spread Air (HAVSD12WSA)

### General

Model	HAVSD12WSA
Length x Width	48 feet x 102 inches
Deck Length	10 feet Front and 38 feet Rear
Rear Deck Height	40 inches - Loaded
Suspension	Wide Spread Air
Frame Rating	80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads
Kingpin Setting	18 inches
Fifth Wheel Height	49 inches
Axle Spread	122 inches - Set at Rear
VIN Plate	Bilingual US/Canadian VIN plate
Estimated Weight	Est. Weight: 11480 lbs. +/-3%

### Structural

<b>Main Beams</b>	<b>130K Load Bearing Flanges</b>
Crossmembers	18 inch Centers Front Deck / 12 inch Centers Rear Deck - 4 inch Jr. I-Steel
Knee Braces	Fabricated on Approx. 60 inch C/C
Side Rails	6 inch Structural Channel @ 6.5 lbs/ft
Stake Pockets	3/16 inch Steel on 24 inch Centers
<b>Pipe Spools</b>	<b>Double Between Stake Pockets</b>
<b>Rubrail</b>	<b>3/8 inch x 2 1/2 inch Steel</b>
Front Corners	Tapered
Bumper	Weld-On; Meets U.S. Underride Requirements
Winch Track	Steel on Road Side; 8-foot Front Deck and Full Length on Rear Deck where Possible
Bulkhead Pockets	4 - F-5 DOT-Type Steel

### Landing Gear

Landing Gear	Jost A400G19 Steel Landing Gear
--------------	---------------------------------

### Flooring

Flooring	1 1/4 inch FIR Wood
----------	---------------------

### Suspension

Suspension Detail	Hendrickson AANL23K Intraax Air Ride
Number of Axles	2
Axle Spindle	Tapered
Brakes	Spring Brakes, Auto Slacks
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums
Wheel Ends	Grease in Hubs - *** 5-Year Wheel End Warranty ***
Tire Inflation System	None Standard
Air Lift	None Standard

### Wheels and Tires

Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD
Tires	255/70R 22.5 16PR OEM Standard tires



### Air System

Air Line Filters	(2) Meritor In-line Type Installed
ABS	4S/2M - No Cable or Tool
Full System Dump	Auto Glad Hand Dump Installed
Electric Dump Valve	Wired to 7-Way Auxiliary Socket to Dump Rear Axle
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer

### Electrical System

Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side

### Paint and Decal

Paint	Black Urethane with Velocity Decals
Conspicuity Tape	Per NHTSA Specs - Installed on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed

### Miscellaneous

Mudflaps	2 Sets OEM Standard; Spring Loaded Brackets Behind Front Axle
Sliding Winches	12 standard: 2 Top Deck - 10 Lower Deck
Winch Location	All Road Side
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Registration Holder	Install Registration Holder - OEM Standard

### Options

Bulkhead	None Standard
Spare Tire Carrier	1 Standard - Mounted Between Lower Gooseneck Beams
Hubodometer	None Standard
Tool Box	None Standard

### Literature

Trailer Literature	<a href="#">Velocity Brochure</a>
--------------------	-----------------------------------

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.