



Hale Trailer Brake & Wheel
 A008369-A008395
 VIN: 553082-553108



Velocity Flat 48 Air Slider (HAVSF12SAT)

General

Model	HAVSF12SAT
Length x Width	48 feet x 102 inches
Suspension	Sliding Air Tandem
Frame Rating	80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads
Kingpin Setting	30 inches
Fifth Wheel Height	49 inches
Axle Spread	49 inches
VIN Plate	Bilingual US/Canadian VIN plate
Estimated Weight	Est. Weight: 11720 lbs. +/-3%

Structural

Main Beams	130K Load Bearing Flanges
Crossmembers	12 inch Centers - 4 inch Jr. I-Steel
Knee Braces	Fabricated on Approx. 60 inch C/C
Side Rails	6 inch Structural Channel @ 6.5 lbs/ft
Stake Pockets	3/16 inch Steel on 24 inch Centers
Pipe Spools	Double Between Stake Pockets
Rubrail	3/8 inch x 2 1/2 inch Steel
Front Corners	Tapered
Bumper	Weld-On; Meets U.S. Underride Requirements
Winch Track	Steel on Road Side
Bulkhead Pockets	4 - F-5 DOT-Type Steel

Landing Gear

Landing Gear	Jost A400G19 Steel Landing Gear with Forward and Rear Bracing
--------------	---

Flooring

Flooring	1 1/4 inch FIR Wood
----------	---------------------

Suspension

Suspension Detail	Hendrickson AAZNT46K Intraax Air Ride Slider - 60 Inches Adjustable
Number of Axles	2
Axle Spindle	Tapered
Brakes	Spring Brakes, Auto Slacks
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums
Wheel Ends	Grease in Hubs - *** 5-Year Wheel End Warranty ***
Tire Inflation System	None Standard
Air Lift	None Standard

Wheels and Tires

Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD
Tires	11R 22.5 14PR OEM Standard tires



Air System

Air Line Filters	(2) Meritor In-line Type Installed
ABS	4S/2M - No Cable or Tool
Full System Dump	Auto Glad Hand Dump Installed
Control Box	Standard Mount of Controls on Slider Frame
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer

Electrical System

Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side

Paint and Decal

Paint	Black Urethane with Velocity Decals
Conspicuity Tape	Per NHTSA Specs - Installed on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed

Miscellaneous

Mudflaps	1 Set OEM Standard
Sliding Winches	12 standard
Winch Location	All Road Side
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Registration Holder	Install Registration Holder - OEM Standard

Options

Bulkhead	None Standard
Spare Tire Carrier	None Standard
Hubodometer	None Standard
Tool Box	None Standard

Literature

Trailer Literature	Velocity Brochure
--------------------	-----------------------------------

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.