



Hale Trailer Brake & Wheel

A008426-A008434

VIN: 37491-37499

Base Model: DF53x102 Air Spread.

Serial #: 37491 - 37499

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' - Base Weight 12,900#

UPPER DECK LENGTH 10'6"

LOWER DECK LENGTH 42'6"

OVERALL WIDTH 8' 6"

KING PIN SETTING 24" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

BULKHEAD None

MAIN FRAME 26" Fab.-PreCannb.I-Beams-(80K Pkg)

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE None

FLOOR DECKING 1-1/8" Apitong

WINCHES 12

STRAPS None

WINCH TRACK Steel Slide Entire Length of Drivers Side

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles

SUSPENSION LOCATION Set 43ft From Kingpin To Rear Axle

AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" Wide Spread

LIFT AXLE None

DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)

TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind All Axles

STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear

PIPE SPOOLS Double •

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

OILFIELD FRONT None

DOCK BUMPERS Rubber Inboard

OILFIELD REAR NECK None

OILFIELD - PIN POCKETS None

DECK ROLLERS None

TAILROLLERS None

CARGO TIE DOWN None

CONTAINER TWIST LOCKS NONE

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

TOOLBOX MATERIAL None

TOOLBOX TYPE None

TOOLBOX LOCATION None

LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear

CUSTOM LIGHTS None

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.