



Hale Trailer Brake & Wheel
A008459-A008467
VIN: 37512-37520

Base Model: EF48x102 Air Slider
Serial #: 37512 - 37520
components description
CAPACITY Standard Package - 80,000 lbs. GVWR (60,000 in 10' Span)
OVERALL LENGTH 48' - 80'Extendable Trailer
OVERALL WIDTH 8' 6"
KING PIN SETTING 24"
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
BULKHEAD None
MAINFRAME 24" Fab. Outer & 17" Fab. Inner - 1/2" x 6" Top & Bottm. Flanges - 1/4" Webs
INTER-FRAME COVER 1/8" Smooth Steel Plate
SIDE RAILS 6" - 6.5# Per Foot
FLOOR SILLS 4" Steel I-Beam 12" O.C. STD Pkg Capacity
FLOOR DECKING 1-1/8" Apitong
WINCH TRACK Steel Slide Entire Length of Drivers Side
WINCHES 12
STRAPS None
LANDING GEAR Two Speed - Jost A500
SUSPENSIONS Air Ride - Tandem Slider - 46K
SUSPENSION LOCATION SliderVariable
AXLES (2) 22.5K Capacity - Type 30 Chambers -Auto Slacks - ABS
AXLE SPACING 49"
LIFT AXLE None
DUMP VALVE Auto Dump All Bags - Gladhand
SCALES None
ABS System Wabco ABS System 2S/1M
PARKING BRAKES All Axles
DUST SHEILDS None
WHEELS Disc- Hub Piloted- 22.5 Steel
TIRES 295/75R 22.5- Double Coin
ANTI-SAIL MUD FLAPS Behind Rear Axle
STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear
RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape
PIPE SPOOLS Double
DOCK BUMPERS Rubber Inboard
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
TIRE CARRIERS None
CUSTOM LIGHTS None
LIGHTS Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.