

## Hale Trailer Brake & Wheel A008555-A008558



## **GENESIS FRAME DUMP**

## VINS: 81218, 81219, 81220, 81221

Length	36'	BODY	SPECIFICATIONS	Body	* ONE 2" LED MARKER I	N
Width	96" INBOARD	Tarp	NONE	Accessories	EACH REAR POST	
Side Height	64" SOLID	Bow Holders	NONE		FACING REARWARD	
Top Rail	9" DUMP RAIL	Tarp Bows	NONE			
Side Matl-front	5'100 WALL	Tarp Basket	NONE			
-middle	25'140 WALL	Tarp Hooks	NONE		TAILGATE	
-rear	6'180 WALL	Bulkhead Mat'l	3/16"	Height	FULL - GENESIS	
Side Options	NONE	Bulkhead	5" SLOPE PLATES	Mat'l Thkness	.140 WALL	
Floor Mat'l	1/4"	Options	D/S-MANDOOR	Slope	NONE	
		Body Fenders	18"	Hinges	OVERSLUNG	
Crsmbr Spacing	10"	Ladders (Out)	D/S-LAST PANEL	Side Swing	YES-W/GRD CTRL-P/S HING	ES
i		ດາມາດການການການການການການການການການການການການການກ		Gateseal	NONE	
Floor Options	STUB LONGITUDINALS	Inside	NONE			
				Safety Latch	ONE EACH SIDE	
		Shovel Hgr	YES- ON FRAME (7)			
Tailgate Control	AIR / FRAME + ELEC CC (1)(2)	U		Coal/Grain Door	r 12" SINGLE HANDLE	
Body Pkg	NONE	Light Panel	FULL - LED; X=LED B/U LIGHTS			
Options			000X 000 X000 (1)	Coal Chute	NONE	
Vibrator	NONE	Marker Lights	LED - 5 PR BOTTOM	Gate Options	NONE	
Mudflaps	STD + (3)	MMTS	BELOW RAIL - LED			
	ACROSS CHASSIS REAR	Apron	NONE			
CHASSIS SPECIFICATIONS						
Model	TRIAXLE- 3 FIXED	ABS	2S / 1M	Tire Carrier	NONE	
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150	
Length	35' 6"				D/S CRANK	
Width	96"	Independ. Susp(s	5)	Chassis Lights	NONE	
Hoist	9-5-265 (4)		NONE			
Chassis Neck	STD			Elec Coupler	7 WAY + 6 WAY	
King Pin Setting	18"	Distance	:			
5th Whl Plate	1/2" W/ 3/8" X 3" X 7" MOUNT	From:		Hyd Tank	NONE	
5th Whl Ht	49"			Hyd Hose Fittin		
Overhang	6"	Controls		Hyd Hose Lengt		
Rear Axle Setting	21.5"			Tow Hooks	TWO-ONE EACH SIDE	
K/P To Rear Axle	386.5"			Paint	EAST BLACK	
Suspension	AAT30K / E3-2-1 (6)	Location				
Susp Control	FRM SWITCH + ELEC CC (1)(2)	Axle(s)				
Susp Spacing	52"					
Susp Options	GALVANIZED HANGERS	Accessories		Chassis	* HINGE SHOES TO HAV	E
Springs	AIR			Options:	REMOTE GREASE ZERK	S
Axles	TP SPINDLES	Brakes			ON D/S.	
Accessories	NONE	Drums			* MUDFLAP ON CHASSIS	3
Brakes Drums	HENDRICKSON MAXX 22T	Hubs			* TAPERED REAR CHAS CROSSMEMBER	SIS
Hubs	10 STUD LW STEEL	Wheels				
14/1	W/ HXL-5;GREASED	<b>T</b> '				
Wheels	8.25 x 24.5 6 HP/ 6 DB (5)	Tires				
Tires	11R 24.5 R250ED H 16 PLY B			Ļ		
			OR TO ESTIMATED BUILD DA			
1. WIRINGTAILGATE WIRED TO AUXILIARY RED-SUSPENSION WIRED TO AUXILIARY BLUE-LED BACK UP LIGHTS WIRED TO AUXILIARY BROWN.						
2. ONE POLYCARBONATE BOX FOR FRAME SWITCHES MOUNTED D/S NEAR LANDING GEAR. AIR IN THE BOX						
3. RUBBER CENTER CHASSIS FLAP AHEAD OF FORWARD AXLE.						
4. HOIST PIN GREASE-REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD. WEIGHT: 14,553						
5. PLASTIC INSULATORS BETWEEN WHEELS/DRUM & WHEELS/HUB						
6. RIGHT WEIGH 2.5" AIR GAUGE IN BOX.						
7. D/S JUST REAR	OF LANDING GEAR FOR SHOW	/EL HANGER TO B	E MOUNTED HORIZONTALLY ON	FRAME.	CHANGE 1	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.