



Hale Trailer Brake & Wheel

A008570-A008574
VINS: 81203-81207



GENESIS FRAME DUMP

Length	36'	BODY SPECIFICATIONS		Body
Width	96" INBOARD	Tarp	NONE	Accessories
Side Height	64" SOLID	Bow Holders	NONE	
Top Rail	9" DUMP	Tarp Bows	NONE	
Side Mat'l-front	7' - .100 WALL	Tarp Basket	NONE	
-middle	23' - .140 WALL	Tarp Hooks	NONE	TAILGATE
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16"	Height
Side Options	NONE	Bulkhead	D/S-MANDOOK	Mat'l Thkness
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Slope
		Body Fenders	14"	Hinges
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Side Swing
		Inside	NONE	Gateseal
Floor Options	STUB LONGITUDINALS	Shovel Hgr	D/S-FRAME	Safety Latch
				Coal/Grain Door
Tailgate Control	AIR / FRAME + ELEC CC (4)	Light Panel	FULL - LED; X=LED B/U LIGHTS	Coal Chute
Body Pkg	NONE		OOOX ooo XOOO	Gate Options
Options		Marker Lights	LED - 14 PR TOP & BOTTOM	REMARK (9)
Vibrator	NONE	MMTS	BELOW RAIL - LED	
Mudflaps	STD + ACROSS REAR (1)	Apron	NONE	

CHASSIS SPECIFICATIONS

Model	TRIAxLE-1 FIXED-FRONT 2 LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	36' 6"				D/S CRANK
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-285 (2)(12)			Elec Coupler	7 WAY + ISO 7 WAY LABELED
Chassis Neck	STD	Distance:			'AUXILIARY'
King Pin Setting	18"	From:		Hyd Tank	NONE
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	Controls		Hyd Hose Fitting	WINGNUT
5th Whl Ht	49"			Hyd Hose Length	108"
Overhang	6"	Location		Tow Hooks	TWO-ONE EACH SIDE
Rear Axle Setting	21.5"	Axle(s)		Paint	BLACK SOFTCOAT
K/P To Rear Axle	398.5"				
Suspension	AAT30K / E3-L(LIFT0-E2-1 (3)(5)	Accessories		Chassis	CHASSIS REAR CM: TAPERED
Susp Control	FRAME + ELEC CC (4)(10)			Options:	W/ DIAMOND PLATE COVER
Susp Spacing	52" - 52" (6)	Brakes			
Susp Options	GALVANIZED HANGERS	Drums			
Springs	AIR				
Axles	TP SPINDLES	Hubs			
Accessories	NONE	Wheels			
Brakes	HENDRICKSON MAXX 22T				
Drums	N/A	Tires			
Hubs	10 STUD STEEL - PILOT				
	W/ HXL-5; GREASED HUBS				
Wheels	8.25 x 24.5 6 HP/ 6 MP				
Tires	11R 24.5 HSR2 16 PLY CONT.(11)				

REMARKS: ALL EAST LOGOS TO BE DECALS ONLY-NOT RIVETTED OR WELDED

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER.-MUDFLAP 4" FORWARD OF STANDARD POSITION.
2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
3. RIGHT WEIGH OIL FILLED GAUGE (LBS.)(FLUSH MOUNT) ON FRONT CHASSIS CROSSMEMBER.
4. WIRED TO AUXILIARY ISO 7 WAY PLUG
5. HEIGHT CONTROL VALVE ON AXLE #3.
6. LIFT AXLES TO BE CONTROLLED THROUGH FRAME SWITCHES & ELEC CC (WIRED TO AUX. PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
7. ALL FRAME SWITCHES TO BE AIR IN A BOX ON D/S NEAR LANDING GEAR. CHANGE 1, 2, 3
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
9. REMOTE GREASE ZERKS FOR LATCH BAR WEIGHT: 14,597
10. CROSSOVER KITS

11. TIREMAXX PRO INFLATION SYSTEM ON ALL THREE AXLES
12. NO ACCESS ON OUTSIDE OF BULKHEAD OR FLAP, ACCESS ONLY ON DOGHOUSE IN INSIDE.
13. HINGE SHOE GREASE ZERKS-REMOTE ZERKS TO D/S MANIFOLD
14. REAR PIN BUSHING LUBE-REMOTE GREASE ZERKS TO D/S MANIFOLD
- 15. NO CAST STEP OR ANY STEP OF ANY KIND BELOW MANDOOR**

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.