

Hale Trailer Brake & Wheel A008607-A008612 VIN: 216602-216607





ITEM	DESCRIPTION
ТҮРЕ	PIN ON AXLE FOR PLATFORM
ITPE	
DIMENSIONS	
LENGTH	61 1/2".
WIDTH	102".
WIDTH	102.
COUPLING	
COUPLER PLATE	For anchor joints, 4 x 2" dia. rods and bushings.
COUPEERFEATE	
STRUCTURE	
FLANGES	1/2" x 6", 100 000 psi steel.
WEB	3/16" plate, 80 000 psi steel. 13 1/2" high.
WEB	
ENDS	
BUMPER	Rectangular steel tubing.
	Including supports with flag and excessif width sign.
	moldaring supports with hag and excessin width sign.
ELECTRICAL	
FRONT CONNECTOR	Cord with 7 ways connector.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra blue LED, sealed beams, in a closed back rubber grommet.
	(tail lights with male pins #54332, markers #47122 (2 1/2" dia.),
	licence light #60280-M).
STROBE LIGHTS	(2), installed (1) on each side, (Grote 77353 amber) (rubber grommet)
SWITCH	Sealed, to activate strobe lights, installed **in the control box**.
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (9), single.
U-BOLTS	With nuts at top.
SPRINGS	Air.
AXLE(S)	Hendrickson, HP-S506, 27 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None (Hendrickson axles).
BRAKES	16 1/2" standard, long life H26-HXS Hendrickson lining.
BEARINGS	HM 518445.
SLACK ADJUSTERS	Meritor, automatic, 28 splines (6").
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), long stroke.
	(4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	WEBB, 10 studs disc hubs, balanced drums 117 lbs,
	outboard mount, 285.75mm B.C., single flange nuts.
	For dual aluminium wheels.
	(Heavy duty 25000 lbs cap.)
RIMS	22.5×8.25 , disc (10 holes),
	285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Continental, 275/70 R 22.5 HSR2 SA 18 ply (38.0")
	$\frac{10000}{1000}$





ITEM	DESCRIPTION
GLAD HANDS	Fix.
AIR VALVES	Sealco, synflex 3/8" diameter.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING	
PAINT	No paint nor primer applied on. Structure prepared and shipped ready to be galvanized. (base 78106100)
AXLE(S) PAINTED	*** PAINTED GRAY ***
HUBS	*** PAINTED GRAY ***
WHEELS OR RIMS	White.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108.
RETROREFLECTIVE TAPES	Gray and red, each side, fully covers rear bumper.
ADDITIONAL OPTIONS UNIT COUPLED TO	SAME AS U#205763 Job:
	This semi-trailer does not comply with GHG regulations. Should GHG
CONFORMITT	regulations come into force prior to the production of the trailer(s),
	Manac will have the obligation to ensure the trailer(s) produced meet
	minimum GHG guidelines. Any modifications required to meet the GHG
	regulations will be added to the initial purchase price and charged back to
	the customer.
1	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.