



**Hale Trailer Brake & Wheel**  
**A009011-A009070**  
**VIN: 034101-034160**



**Product : , , ,**

**GVWR**

GVWR: Trailer to meet 68,000 Pound GVWR  
 VIN PLATE: US - VIN Plate to Read in English (Standard)  
 \* Product Type: HT HyCube

**GEOMETRY**

Length - Exterior: 53'-0"  
 \*\* Length - Interior: 52'-6" Nominal Lining To Lining  
 Width - Exterior: 102.36"  
 \*\* Width - Interior: 101" Nominal Lining To Lining  
 Height - Exterior: 13'-6"  
 Height - Interior: 110" Nominal  
 Deck Height: Standard application  
 Fifth Wheel Height: 47"  
 King Pin Location: 36"  
 Landing Gear Location: 107" from King Pin (+ 1"/-1/4")

**TIRES & WHEELS**

Tire Furnished: Factory Furnished  
 \* Tire Manufacturer: Hankook TL21(G), Low Rolling Resistance Tire  
 Tire Size: 295/75R22.5  
 Wheel Furnish: Factory Furnished  
 Wheel Material: All Steel Wheel  
 Wheel Manufacturer: HT Standard (TCC 361)  
 Wheel Size: 8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)  
 \* Wheel Finish for Steel: Hot Dip Galvanized.  
 Tire Stem Valve Position: Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)  
 Wheel Finish for Aluminum: None (Due to All Steel Wheel Application)  
 \* Valve Stem & Cap: TR-572 Valve Stem# 8900HALNC for use w/PSI; w/o Cap

**UPPER COUPLER**

Approach Plate: 1/4" thick 80,000 Lb Yield - 6 Support Channels  
 King Pin (BTM Main) Plate: 1/4" thick 80,000 Lb Yield  
 King Pin & Manufacturer: Standard (Jost) AAR Cruciform King Pin  
 \* Front Bottom Rail: Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle  
 Upper Coupler Tube Qt'y: (1) Tubing Application - Joggled

**BODY/BASE**

Forward Crossmember: Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L  
 Landing Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)  
 Bay Area Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L  
 Running Gear C/M Size: 4" High  
 Running Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'  
 Slider Body Rail (VT): 208" Rail Length

**FLOOR**

Upper Coupler Type: 3.40" Joggled with Exposed Coupler Top Plate (New STD)  
 Floor Specification: 1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood  
 Floor Ratings - VT: 18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating

Floor- Assembly Method: Wood Floor Assembly  
Floor Screws: (3) 0.31" Dia. screws per Board on I beams  
Threshold-Finish: Hot Dip Galvanized  
Threshold Plate: 0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts  
Threshold-Application: Standard Application

**FRONT**

Front Corner Radius: 4" Extruded Aluminum  
Front Panel & Color - Dry: 0.05" Aluminum Prepainted White w/ natural color rivets  
Front Corner Mat'l - Dry: Extruded Aluminum  
Front Posts: (4) 2.5" Deep (16Ga) Steel Hats - Non AAR  
Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid  
Front Receptacle(7-Way): Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug  
Front Receptacle(7-Way) - Options: Phillips QCS Plug connector  
Gladhand/7-Way Location: Overlaid on Lower Roadside Front  
\* Corner Radius Protector: (2) 0.125" X 12" Alum Diamond Plate Each Side at Top

**SIDE**

\* Side Material: 0.05" Aluminum Prepainted White w/ natural color rivets  
\* Side Posts: 0.45" Deep 14 Gauge Galv Steel "A" Slotted Logistic Posts  
\* Side Post Centers: 16" C/L with 12" C/L @ Upper Coupler and Support Gear  
\* Side Top Rail: Shallow Post Side Top Rail  
\* Side Bottom Rail: Side Bottom Rail STD  
Fasteners to Bottom Rail: Standard Rivets to attach C/Members to the Side Bottom Rail  
\* Side Sub Options: Additional A-Slotted holes in Rearmost Position to use as Logistic Slots

**REAR**

Rear Frame: Swing Door, 2.5" New Door Header Standard Trailers (with 1 Lock Rod Per LH & RH Door)  
Rear Door Opening Spec.: Standard Application  
Floor Level: Door to be Flush with Floor (STD)  
Door Type for Dry Van - SW: 0.5" Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin  
\* Option - Door (Main Line): Install Standard Anti-Theft Hardware  
Option - Door Install Instruct: Standard Door Installation per Manufacturer's Recommendation  
Option - Door & Hardware: One(1) Rubber Door Bumper Standard (1" Deep) on Hinge of each Swing Door  
Door Holder Type for Swing Door: Standard Door Holdback  
\* Hinges: Four (4) Aluminum Hinges per Door  
\* Additional Hinge Option: Additional One(1) Aluminum Hinge (Total 5 Per Door)  
\* Rear Underride Guard: 4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG) 30  
Option - Horiz Member/Other: One piece roll formed w/continuous welding  
Underide Bolt Spec.: Zinc plated bolts & nuts - Standard  
Dock Bumper: Pair 3" X 6" Mold Bolted Bumper  
Rubber Bumper Location: Inboard of Light Protector Bars (Standard)

**LIFT GATE**

**ROOF**

Roof Panel: 0.040" Aluminum  
Roof Bow: 16 Gauge Galvanized Steel Anti-Snag  
Roof Bow Centers: 24" Centers Full Length

**LINING/SCUFF**

\* Side Lining: 0.235" HDPE Recycled Plastic Installed between Posts  
Front Lining: 0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height  
\* Base Side Scuff: 0.63" x 12" High White Recycled Plastic  
\* Mounting Method: Mounted Directly to Posts  
\* Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)

**LANDING GEAR**

L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG

L/Gear Mt'g Method:	Inboard Mounting (Standard)
L/Gear Shoes:	10" X 10" RCF (Removable Cushion Foot) Low Profile
L/Gear Ground Clearance:	Nom. 12" Ground Clearance
L/Gear Mt'g Bracket:	Hot Dip Galvanized Large Wing Plate
L/Gear Crank Handle:	Roadside
L/Gear Options:	None (HT STD)
L/Gear Cross Brace Design:	HT Standard Cross Brace attachment Design

#### RUNNING GEAR

Bogie Type:	Sliding Tandem(2) Axle Bogie
Axle Spacing:	49" Axle Spacing
Axle ABS System:	Tandem Axle w/2S1M ABS System
Bogie & Axle Location:	Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
Option-Related Bogie Stopper Feature:	STD plug stopper
Susp. Manufacturer:	Hendrickson
Suspension Capacity:	Standard Duty
Hendrickson Susp. Specification:	Hendrickson Vantraxx HKANT40K Air Ride
Surelok (Anti-Dock):	Surelok (Anti-Dock) Installed
Locking Pin Mechanism:	Air-Assist Pin Puller or Quik Draw
Susp. Sub-Frame:	Hendrickson K-2 STD Duty
Type of Susp Spring:	Air Bag
Spring Specification:	Air Bag
* Axle Diameter:	5.75"
Axle Supplier:	Hendrickson
Axle-General Spec.:	Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
Axle-Track Length:	77-1/2"
Axle-Spindle Type:	Tapered Spindle
Brake Lining Size:	16.5" X 7"
Brake Lining Spec.:	Hendrickson Extended Service (Abex-3030-197)
Brake Control System:	2S/1M Wabco ABS
Spring Brake Control:	Sealco 110500 Springbrake Priority
Brake Cont-Hose & etc.:	Standard Air Line & Hose Application (US&Canada)
* Slack Adjuster Spec.:	Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
* Brake Chamber Spec.:	Wabco Premium Chamber
* Stroke Length:	3" Long Stroke Length
Hub Specification:	HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
Drum Specification:	HT Standard (KIC) Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco
* Lubrication Spec.:	Chev Delo (Syn) Grease
* Wheel Seals Spec.:	Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
* Tire Inflation Spec.:	Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
Tire Inflation Pressure:	100 PSI
* Tire Inflation Lamp Location:	Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
* Tire Inflation Lamp Spec.:	33 Series Lamp

#### ELECTRICAL

Harness-General Spec.:	Molded Color Code Phillips Harness with QCS Plug
Harness-Special Feature:	Manufacturer's Standard Feature
Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket

Rear Side Marker Detail Spec: (2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware  
Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD  
S/T/Tail Light-Quantity & Type: (4) Trucklite 40 or 44 Series (Round Style) or Equivalent  
S/T/Tail Light-Detail Spec: (4) Trucklite 44331R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets  
Main Mid-Turn Light: Install the Mid turn lamp  
Mid-Turn Mounting Method: Mounting Bracket  
\* Main Mid-Turn Light-Detail Spec: (2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets  
ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware  
ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD  
License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange  
Option Related Harness/Wiring: Standard  
Electrical Related Regulation: Standard Application

**MARKING/DECALS**

HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)  
Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes  
Decal Opt 2-Decal Location: Standard Application  
Decal Opt 3-Decal Installation: Standard Application  
\* Conspicuity Vendor: Avery  
Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail  
License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate  
License Plate Brk't Install: Standard Install Location - Roadside Below Door Sill  
Furnish Document Holder: Factory Furnished  
Document Holder Detail Spec: (1) Phillips 16-802  
\* Document Holder/Manifest Loc.: Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

**PAIN/FINISH**

\* Upper Coupler Finish: Galvanized-Whole upper coupler section  
\* Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)  
\* Axle & Components Finish: Black Undercoating  
\* Susp. Sub-Frame Finish: Black Undercoating  
L/Gear(K-Bracing) Finish: Hot Dip Galvanized  
\* L/Gear(Upper Leg) Finish: Hot Dip Galvanized  
Rear Frame-Finish: Hot Dip Galvanized  
Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)  
Rear Underride-Finish & Spec.: Hot Dip Galvanized & Welded Horizontal Member  
Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider: Factory Furnished Mudflaps  
Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo  
Mudflap Mounting Loc.: Suspension Frame  
Mudflap Mounting: STD Location w/ H.D Washer Retainer  
\* Lift Pad Spec.: Install HT Occasional use lift pads for delivery, with HYUZ decals

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.