

# HALE

## TRAILER

### BRAKE & WHEEL



Hale Trailer Brake & Wheel  
 A009137-A009146  
 VIN: S008803-S008812

**TK80SA 2 axle Sliding Axle trailer; 80,000 lbs uniform / 50,000 lbs in 10 ft.**

**17333-80SA**

17333 - STANDARD EQUIPMENT  
 Perimeter Frame Gooseneck Design  
 Hydraulic sliding axles  
 Tilting main deck - forms a ramp to upper deck  
 No traveling hydraulic lines for sliding axle operation  
 Side by side 2-stage cylinder, closed in travel position

Air and electrical lines contained in protective track  
 Single recessed winch roller at front of deck  
 4 beam main frame construction  
 Rubber mounted sealed lights with sealed harness system  
 Red & white conspicuity markings

Item #	Category	Description	Weight (lbs)	Qty
17333	Open Deck	TK80SA 2 axle Sliding Axle trailer; 80,000 lbs uniform / 50,000 lbs in 10 ft.		
17336	Overall Length	49'-11" overall length		
17339	Overall Width	102" wide		
17342	Fifth Wheel / King Pin	49" loaded fifth wheel height		
17345	Upper Deck	9'0" Straight drop upper deck (14" kingpin setting with 86" swing clearance)		
17346	Upper Deck	No Headboard		
17350	Upper Deck	2 side access tool boxes at front of upper deck		
17352	Winch	20,000 lb. hydraulic winch with level wind (mounted above king pin) Includes 9/16 x 80' cable		

17358	Winch	Delete Winch guard	(61)	
17359	Winch	Winch Cable Skid Plate on Upper Deck		
17362	Hydraulics / Controls	PTO hydraulic tilt		
17366	Hydraulics / Controls	Push - Pull style hydraulic valve controls w/ full-function wireless remote controls (Dual side controls)		
17367	Landing Gear	2 Speed park stands (crank road side)		
17370	Main Deck	Triangle cutouts		
17371	Main Deck	3" crossmembers on 12" Cross member spacing centers		
17374	Main Deck	Approximately 7 degree load angle / 15 degree dump angle (17.5 tires & 48' OAL trailer)		
17375	Decking, Main Deck	1 3/8" (NET) apitong deck raised		
17380	Decking, Approach Plate	3/8" smooth approach plate with 4-way slots on approach plate		
17383	Tie Downs	Internal 2-way key slots on approximately 24" centers length of trailer in inner and outer beams		
17390	Suspensions / Axles	Air Ride suspension		
17391	Suspensions / Axles	Air Ride raise & lowering control panel on upper deck with liquid filled guage		
17392	Suspensions / Axles	25,000 lb. capacity axles		
17401	Axle Spacing	50" Axle Spacing		
17404	Brakes	12.25 X 7.5 Drum brakes (For 37.5" deck height, select 17.5 wheels and tires)		
17405	Brakes	4S2M ABS Brakes		
17406	Hub / Drum	Steel hub-piloted - Cast drum - tapered spindle (per complete axle)		
08182	Wheels (inside)	6.75 x 17.5 8-hole steel disc wheel		4
15004	Wheels (outside)	6.75 x 17.5 8-hole polished (XP) aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel	(96)	4

10058	Spare Wheel	No Spare Wheel		
18103	Tires	Continental 235/75R17.5 HTL2 - 18 ply (tire only) (per tire) ILO Std Continental 245/70R17.5 HTL2 - 18 ply	(544)	8
10059	Spare Tires	No spare tire		
17412	Flaps, Mud Guards & Fenders	Mudflaps		
17413	Lights / Electrical	Grote Electrical system (meets DOT regulations)		
17414	Lights / Electrical	Single Mid-turn signal w/ clearance lights X-O-X (whole trailer)		
17416	Lights / Electrical	3rd tail light package		
17422	Flagholder s	Flag Holders at rear of trailer		
17424	Miscellaneous	Central located lube system		
08009	Paint	Epoxy primer		
08030	Paint	S7205 IH Red with white decals		

### 17333-Additional Options

Item #	Category	Description	Weight (lbs)	Qty
17395	Suspensions / Axles	PSI Tire Inflation System (2 axle)		
17433	Miscellaneous	Fold-down step and handle road side		
17434	Miscellaneous	Fold-down step and handle curb side		

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.